

070-00033
[Redacted]

Texas Instruments Incorporated Attleboro, Massachusetts

Remediation of the Former Radioactive Waste Burial Site (NRC License SNM-23)

Final Report

Prepared by

Creative Pollution Solutions, Inc.
September 1993

SECTION COPY

118045

11-05-93

Table of Contents

| | | |
|--------|---|----|
| 1.0 | Background Information | 1 |
| 1.1 | Nuclear Operations | 1 |
| 1.2 | Summary of Radiological Surveys | 1 |
| 2.0 | Site Description | 3 |
| 2.1 | General Description | 3 |
| 2.2 | Survey Findings | 4 |
| 2.2.1 | Background Levels and Baseline Concentrations | 4 |
| 2.2.2 | Burial Area Findings -- ORAU Survey | 5 |
| 2.2.3 | Burial Area Findings -- CPS Surveys | 6 |
| 3.0 | Management Commitment and Project Organization | 7 |
| 3.1 | Management Policy | 7 |
| 3.2 | Project Organization | 8 |
| 4.0 | Remediation Activities | 8 |
| 4.1 | Remediation Criteria | 8 |
| 4.2 | Contaminants Identified | 9 |
| 4.3 | Previous Radiological Surveys | 9 |
| 4.4 | Chronology of Site Operations | 9 |
| 4.4.1 | Pilot Study | 10 |
| 4.4.2 | Initial Remediation Estimates | 10 |
| 4.4.3 | Pre-Excavation Survey | 11 |
| 4.4.4 | Revised Remediation Estimates | 11 |
| 4.4.5 | Initial Excavation | 12 |
| 4.4.6 | Adjustment in Approach to Remediation | 13 |
| 4.4.7 | Initial NRC/ORISE Site Visit | 14 |
| 4.4.8 | Extending the Bounds of the Excavation | 14 |
| 4.4.9 | Scraping the Floor of the Excavation | 15 |
| 4.4.10 | NRC Survey | 16 |
| 4.4.11 | Topographical Survey | 16 |
| 4.4.12 | Backfilling | 16 |
| 5.0 | Final Survey | 17 |
| 5.1 | Introduction | 17 |
| 5.2 | Perimeter Split Spoon Sampling | 17 |
| 5.3 | Surface Soil Sampling within the Excavated Area | 17 |
| 5.4 | Walkover Surveys of the Burial Area | 18 |
| 6.0 | Conclusion | 18 |

List of Figures

- Figure 2.1 Map of Massachusetts and Attleboro Showing Location and Plan View of the Texas Instrument Site
- Figure 2.2 Defined Burial Area
- Figure 2.3 Burial Area With Grid Layout
- Figure 2.4 Pilot Survey Site Layout
- Figure 3.1 Organizational Chart
- Figure 4.1 Project Timeline
- Figure 4.2 Control Zone Layout
- Figure 4.3 Extent of Excavation as of November 28, 1992
- Figure 4.4 Final Site Excavation
- Figure 5.1 Split Spoon Sample Locations
- Figure 5.2 Location of Samples from the Floor of Excavated Area

List of Appendices

- Appendix A Health and Safety Activities During Remediation of the Texas Instruments Incorporated Attleboro Site
- Appendix B Waste Characterization, Manifesting, and Disposal
- Appendix C Radiological Field Screening for Uranium in Soil
- Appendix D Bore Locations and Data Sheets
- Appendix E Final Survey Methods and Results
- Appendix F Site Hydrogeology
- Appendix G "Radiological Characterization of Texas Instruments Incorporated Attleboro Industrial Facility, Attleboro, Massachusetts"
- Appendix H "Preliminary Cost Estimates of Various Remediation Options for Texas Instruments Incorporated, Attleboro, Massachusetts"
- Appendix I "Supplemental Sub Surface Sampling and New Cost Estimates for the Environmental Restoration Program of the Texas Instruments Incorporated, Attleboro Site"
- Appendix J "Texas Instruments Incorporated Remediation Plan"
- Appendix K NRC Correspondence and Inspection Reports

Appendix A Health and Safety Activities During Remediation of the Texas Instruments Incorporated Attleboro Site

| | |
|---------------|--|
| Attachment A1 | Health and Safety Plan |
| Attachment A2 | Air Sampling Methodology and Analysis |
| Attachment A3 | Breathing Zone Air Sampling Methodology and Analysis |
| Attachment A4 | Bioassay |
| Attachment A5 | Personnel Dosimetry |
| Attachment A6 | Radiological Survey |

Appendix B Waste Characterization, Manifesting, and Disposal

| |
|---|
| Physical Description of Waste |
| Waste Site Requirements |
| Waste Characterization |
| Packaging, Marking, Labeling, Shipping, and Manifesting |
| Summary Table of Shipments |

| | |
|--------------|--|
| Attachment 1 | EnviroCare License and Site Requirements |
| Attachment 2 | Waste Profile Analysis |
| Attachment 3 | Waste Classification |
| Attachment 4 | Conrail Instructions |
| Attachment 5 | Spreadsheets Used for the Generation of RSRs |
| 5-1 | Shipment 1 |
| 5-2 | Shipment 2 |
| 5-3 | Shipment 3 |
| 5-4 | Shipment 4 |
| 5-5 | Shipment 5 |
| 5-6 | Shipment 6 |
| 5-7 | Shipment 7 |
| 5-8 | Shipment 8 |
| 5-9 | Shipment 9 |
| 5-10 | Shipment 10 |
| Attachment 6 | Emergency Response and Instruction to Drivers... |

Appendix C Radiological Field Screening for Uranium in Soil

- 1.0 Introduction
- 2.0 GM Screening Technique
- 3.0 Gross Alpha Screening Technique
 - 3.1 Introduction
 - 3.2 Sample counting Equipment
 - 3.3 Sample Preparation
 - 3.4 Sample Counting and System Evaluation
 - 3.5 Sample Variability
 - 3.6 Sample Collection in the Field
 - 3.7 Initial Alpha Screening Correlation
 - 3.8 Additional Alpha Screening Correlations
- 4.0 Conclusions

List of Figures

- Figure C-1 Analysis of GM Detector Response to Varying Soil Mass
- Figure C-2 Gamma Spectroscopy versus Alpha Screening
- Figure C-3 Alpha Spectroscopy versus Alpha Screening
- Figure C-4 Alpha Screening Correlation with Uranium in Soil
- Figure C-5 Comparison of Total Uranium Analysis Results

List of Tables

- Table C-1 Repetitive Counts on Single Sample
- Table C-2 Independent Progeny Counts from Parent Sample
- Table C-3 Individual Progeny Samples from Process Pile

List of Attachments

- Attachment 1 Gross Alpha Screening Data

Appendix D Bore Locations and Data Sheets

- Attachment 1 Drilling Location Listing and Diagrams
- Attachment 2 Drilling Log Sheets

Appendix E Final Survey Methods and Results

Introduction

Walk-Over Near Surface Survey

One Meter Gamma Survey

Surface Soil Sampling

Split Spoon Sampling

List of Tables

Table 1: Walkover Survey Results

Table 2: One Meter Exposure Rate Measurements at Grid Intersections

Table 3: Excavated Area Soil Sample Results

Table 4: Grid Cell Averages of Gross Alpha Screening Data

Table 5: Perimeter Split Spoon Sample Results

List of Figures

Figure 1: Surface Soil Locations Within Excavated Area

Figure 2: Split Spoon Sampling Locations

List of Attachments

Attachment 1 Post Excavation Radiological Survey Report

Attachment 2 Revised Final Survey Report

Appendix F Site Hydrogeology

1.0 Pass investigations and documentation

2.0 Hydrogeological setting

3.0 Potential contaminant fate and transport

4.0 Conclusions

List of Attachments

Attachment 1 "List of documents containing hydrogeological information"

List of Tables

Table F-1 Post remediation groundwater sampling data from locations around the burial area

Table F-2 Dewatering of the excavation site data

List of Figures

Figure 1 Groundwater monitoring well locations

Figure 2 Potentiometric map of overburden aquifer

Appendix G "Radiological Characterization of Texas Instruments Incorporated Attleboro Industrial Facility, Attleboro, Massachusetts"

Appendix H "Preliminary Cost Estimates of Various Remediation Options for Texas Instruments Incorporated, Attleboro, Massachusetts"

Appendix I "Supplemental Sub Surface Sampling and New Cost Estimates for the Environmental Restoration Program of the Texas Instruments Incorporated, Attleboro Site"

Appendix J "Texas Instruments Incorporated Remediation Plan"

Appendix K NRC Correspondence and Inspection Reports

**TEXAS INSTRUMENTS INCORPORATED
FINAL REPORT: REMEDIATION OF THE FORMER
RADIOACTIVE WASTE BURIAL SITE**

License: SNM-23
Docket No: 70-33

Date: September 1993
Version: 1.0

1.0 BACKGROUND INFORMATION

1.1 Nuclear Operations

The Texas Instruments Incorporated (TI), Attleboro, Massachusetts site was owned and operated by Metals & Controls, Inc. (M & C) until 1959, at which time M & C merged with TI. The General Plate Division of M & C began processing nuclear materials in 1952, and between 1952 and 1959 fabricated uranium foils for reactor experiments and fuel components and complete reactor fuel cores for the U.S. Navy. Source material license D-549 was issued permitting acquisition and title to refined source material for use in the production of the uranium foils; and special nuclear materials license No. SNM-23 was issued, permitting acquisition and title to enriched uranium for fabrication of the fuel components and cores. After the merger in 1959, TI continued fabricating reactor fuel cores, for government research and production reactors in addition to the nuclear Navy program. Also, source materials (e.g., natural uranium and thorium) were used under the same programs. TI's involvement in the nuclear Navy business continued into 1966. The final chapter of TI's nuclear business involved the fabrication of High Flux Isotope Reactor fuels (HFIR). The HFIR project extended for approximately thirteen years between 1968 - 1981.

On-site burials of scrap materials contaminated with uranium were conducted at the Texas Instruments Incorporated site in accordance with 10 CFR 20.304. The former radioactive waste burial site was believed to have operated from approximately 1958 through 1961, however materials found during the 1992 excavation suggest the first burials may have occurred in the early 1950's.

Work with nuclear materials was gradually reduced beginning in 1968 and was terminated in 1974. The interior of the facility (buildings 3, 4 and 10) was decontaminated and released for unrestricted use by the Nuclear Regulatory Commission (NRC) in 1983.

1.2 Summary of Radiological Surveys

In 1982 and 1983, TI conducted two radiological surveys in and around the location of the former radioactive waste burial site. Both studies indicated that residual levels were within regulatory guidance established by the NRC, Option 1-4 of the Branch Technical Position (Federal Register v.46,n.205, 23 October, 1981, pg 52061-52063, "Disposal or On-Site Storage

**TEXAS INSTRUMENTS INCORPORATED
FINAL REPORT: REMEDIATION OF THE FORMER
RADIOACTIVE WASTE BURIAL SITE**

License: SNM-23
Docket No: 70-33

Date: September 1993
Version: 1.0

of Thorium or Uranium Wastes from past Operations.") The second study further recommended that the former burial site should remain intact and undisturbed as all contaminated material was buried and reasonably inaccessible.

A follow-up verification study by the NRC (1985) identified some "isolated" pockets of surface and sub-surface contamination. The Oak Ridge Associated Universities (ORAU) study¹ reiterated much of what was already known from the TI radiological surveys. Data from the ORAU study suggested that the majority of the residual radioactivity was associated with small fragments of metal and other scrap material discernable from the surrounding soil particles. Furthermore, most of the contamination was found within the first few feet of the surface. Radioactivity was not found to be migrating with the groundwater flow. The report concluded, however, that there were isolated pockets of surface and subsurface contamination that exceeded the limits allowed by the NRC under Option 1 of the Branch Technical Position (BTP). Option 1 prescribes levels acceptable for release with no restrictions. As a result of these findings, the ORAU study virtually eliminated the possibility of terminating the SNM license without some degree of remediation.

In the summer of 1992 additional surveys of the burial site were performed by Creative Pollution Solutions, Inc. (CPS), a radiological consulting firm, to better determine the levels of residual activity and the extent of contamination in preparation for remediation within the burial area.

The results of the ORAU survey along with the CPS survey results were the basis for estimating areas requiring remediation and projecting volumes of soil for disposition. Remediation of the burial area began on August 31, 1992.

Radiological surveys were performed to demonstrate that Option 1 of the BTP had been achieved. These surveys were initiated in November 1992. Following submittal of the results of these surveys, on-site verification surveys were performed by both the NRC and Oak Ridge Institute for Science and Education (ORISE).

¹ Radiological Survey of the Texas Instruments Site, Attleboro, Massachusetts, Final Report, January 1985, Oak Ridge Associated Universities, Report Number RSAP/ SMPB-8

**TEXAS INSTRUMENTS INCORPORATED
FINAL REPORT: REMEDIATION OF THE FORMER
RADIOACTIVE WASTE BURIAL SITE**

License: SNM-23
Docket No: 70-33

Date: September 1993
Version: 1.0

This report describes the results of these surveys and demonstrates that the former radioactive waste burial site now satisfies the NRC guidelines for release for unrestricted use. These surveys are detailed in this report.

2.0 SITE DESCRIPTION

2.1 General Description

The Texas Instruments Incorporated, Attleboro, Massachusetts, site is located approximately 48 kilometers south of Boston on Route 123. The area of concern was the area between buildings 11 and 12, to the southwest of building 12 (see Figure 2.1).

The area of concern for remediation activities was believed to be within an area previously defined as the burial area (see Figure 2.2). This defined boundary covers an area of approximately 10,000 m². This was the area within which the burials described in section 1.1 of this report took place. The actual excavation covered an area of approximately 2500 to 3000 m².

The burials were believed to be at least 1.2 m deep and covered with a soil cap of unknown thickness. There is no indication that any liner material was used. The site was disturbed during construction of Building 12, and contaminated soil from the original burial trenches was apparently distributed over a larger area. For this reason, the area of concern was the larger burial area (approximately 10,000 m²). This area was fairly level and clear of obstructions, with the exception of some landscaping details and a five foot wide concrete sidewalk located parallel and along the 170 North gridline. The area was bounded by a bog on the north northeast side (see Figure 2.2) and by buildings and paved areas for the remaining areas. For this report "burial area" refers to this larger area, and "burial site" refers to the smaller area requiring excavation.

The underground utilities between buildings 11 and 12 were of concern since excavation affected that area. The utilities in the area included a 8 inch gas line, three air lines, a 12 inch water main, a sewer main, a telephone cable, and a communication duct.

**TEXAS INSTRUMENTS INCORPORATED
FINAL REPORT: REMEDIATION OF THE FORMER
RADIOACTIVE WASTE BURIAL SITE**

License: SNM-23
Docket No: 70-33

Date: September 1993
Version: 1.0

The site hydrogeology has been well documented by subsurface investigations initiated for concerns over non radiological groundwater contaminants elsewhere at the Attleboro site. The burial area is located at a groundwater flow divide and thus the hydraulic gradient is relatively flat. As a result of this condition the groundwater flow rates at this location are extremely slow. Further discussion of the hydrogeology and other water sampling are found in Appendix F.

2.2 Survey Findings

2.2.1 *Background Levels and Baseline Concentrations*

The ORAU survey reported background exposure rates and dose rates along with baseline radionuclide concentrations in soil and water for five locations, from the Attleboro area (but not on or near TI property). The reported exposure rates ranged from 10-11 $\mu\text{R/h}$, both at contact and at 1 meter above the surface. Dose rates measured at the surface ranged from 21 to 31 $\mu\text{rad/h}$.

Soil samples were obtained and analyzed isotopically. The soil concentration ranges for the radionuclides of interest were: U-235, <0.11 to <0.34 pCi/g (picocuries per gram); U-238, <0.78 to 2.74 pCi/g; Th-232, 0.54 to 1.23 pCi/g; and Ra-226, 0.41 to 0.84 pCi/g.

Ground water samples were analyzed for gross alpha and beta concentrations. These samples ranged from <0.32 to 0.59 pCi/l (picocuries per liter) and 1.42 to 3.07 pCi/l, respectively.

These levels and concentrations are typical of those normally occurring in nature. As part of the remedial activities CPS also collected a background soil sample from an area in Attleboro (but not on or near TI property). This sample was submitted for alpha spectrographic analysis. Concentrations of radionuclides in this background soil sample were: U-235 - 0.025 pCi/g, U-238 - 0.7 pCi/g and U-234 - 0.7 pCi/g .

**TEXAS INSTRUMENTS INCORPORATED
FINAL REPORT: REMEDIATION OF THE FORMER
RADIOACTIVE WASTE BURIAL SITE**

License: SNM-23
Docket No: 70-33

Date: September 1993
Version: 1.0

2.2.2 Burial Area Findings -- ORAU Survey (1984)

During the ORAU survey, direct radiation levels were measured at grid line intersections throughout the burial area (see Figure 2.3). The gamma exposure rates measured at 1 m above the surface ranged from 10 to 13 $\mu\text{R/h}$. At surface contact, the exposure rates ranged from 10 to 14 $\mu\text{R/h}$. In addition to the grid line measurements ORAU also identified numerous small areas with slightly elevated surface radiation levels. Contact gamma exposure rates ranged from 16 to 200 $\mu\text{R/h}$.

Surface soil samples were taken at alternate grid line intersections. These samples contained U-235 and U-238 soil concentrations ranging from <0.11 to 8.15 pCi/g and <0.38 to 44.9 pCi/g respectively. The highest value of U-235 and U-238 were identified at locations 235N x 165E and 165N x 125E respectively.

Surface soil samples were also taken in the areas identified as having elevated contact radiation levels. Concentrations of U-235 ranged from <1.78 to 590 pCi/g. The maximum level was in the sample collected at 185N x 149E. Concentrations of U-238 ranged from <46.6 to 887 pCi/g. The maximum level was found in the sample collected at 154N x 111E.

Radionuclide concentrations in subsurface soils were determined by taking samples from several boreholes within the burial area. Elevated concentrations of U-235 were determined ranging from 6.03 pCi/g to 20.6 pCi/g. Elevated concentrations of U-238 were determined ranging from 5.48 pCi/g to 680 pCi/g.

Subsurface water samples were also taken from the boreholes. At seven locations outside of the burial area, gross alpha and beta concentrations were slightly elevated above baseline concentrations. Gross alpha concentrations ranged from 1.36 to 8.66 pCi/l, and gross beta concentrations ranged from 3.03 to 14.0 pCi/l. Additionally, water samples were collected from four locations in the burial area. The gross alpha concentrations ranged from 1.21 to 101 pCi/l and the gross beta concentrations ranged from 6.20 to 251 pCi/l. Though these levels appear to be elevated compared to other samples taken, the aqueous samples were not filtered prior to analysis. Subsequent sampling in 1993 provides a better characterization of groundwater quality. (see Appendix F)

U-235
1-235
5.48
680
pCi
U-238
6-20.6

**TEXAS INSTRUMENTS INCORPORATED
FINAL REPORT: REMEDIATION OF THE FORMER
RADIOACTIVE WASTE BURIAL SITE**

License: SNM-23
Docket No: 70-33

Date: September 1993
Version: 1.0

2.2.3 *Burial Area Findings -- CPS Surveys (1992)*

The pre-excavation surveys performed by CPS, Inc. included a pilot study ("Radiological Characterization of Texas Instruments Incorporated", 7/92 Appendix G) and a subsurface sampling study ("Supplemental Subsurface soil sampling ...", 8/92 Appendix I). These surveys did not include walkover surveys, water sampling or ground water sampling since the ORAU study appeared to adequately cover these aspects of the survey.

In the pilot study a trenching scheme was used in an attempt to better determine the extent and depth of contamination. The trenches along with a few test pits were excavated in the areas shown in Figure 2.4. The concentration of total uranium in soil samples obtained during the pilot study, based on alpha screening results, ranged from 8.22 to 3349 pCi/g total uranium. Specifically the concentrations of total uranium in samples from trench A, B, C and D ranged from 9.06 to 44.88 pCi/g , 8.22 to 27.99 pCi/g , 20.34 to 84.66 pCi/g , and 14.18 to 3349 pCi/g respectively. The concentrations in samples from the test pits ranged from 11.24 to 117.63 pCi/g total uranium. The highest concentration identified was found in the "D trench" at 170N x 130E. This sample was found at approximately 3 - 4 feet depth. The high end concentrations were found in only a few samples.

The subsurface sampling survey included selected sample locations based on previous elevated samples and random sample locations selected within the burial area. The concentration of total uranium in soil, based on alpha screening results, ranged from 8 pCi/g total uranium to 227 pCi/g total uranium. Thirty one samples, from nineteen locations, were identified above the 30 pCi/g criteria however, only four showed concentrations greater than 200 pCi/g total uranium. The results of this subsurface soil sampling are detailed in Appendix I.

**TEXAS INSTRUMENTS INCORPORATED
FINAL REPORT: REMEDIATION OF THE FORMER
RADIOACTIVE WASTE BURIAL SITE**

License: SNM-23
Docket No: 70-33

Date: September 1993
Version: 1.0

3.0 MANAGEMENT COMMITMENT AND PROJECT ORGANIZATION

3.1 Management Policy

From the outset of the project, TI established the goal to remediate the former radioactive waste burial site to the levels prescribed in Option 1 of the BTP. Originally, initial estimates, in the most optimistic scenario, projected the volume of soil and debris requiring disposal would not exceed 10,000 cubic feet. In the end, the actual volume of soil disposed proved to be approximately 63,000 cubic feet. Though the scope of the project expanded to this degree, TI remained committed to achieving Option 1 criteria within the burial area.

The health and safety procedures and policies implemented during the site operations took priority over all other site operations. A conservative approach was always exercised with regard to personnel and environmental monitoring. During the site excavation, twenty-four hour security was maintained to protect the public from the physical dangers of an excavation site. After the excavation process was complete and prior to backfilling, a temporary, six foot high chain link fence was erected to prevent unauthorized access to the burial area.

In order to provide positive public relations, TI proactively disseminated information to the media, public officials and the site workforce. Prior to the physical excavation TI issued a press release which explained exactly what contaminants were involved on the site and what measures were being taken to rectify the problem. As the time period over which the physical excavation took place was extended, TI issued periodic updates. The Environmental Department of TI routinely conducted management and supervisor briefings to update site personnel on the status of the project.

To assist in all of the above, TI established a Task Force which met on a weekly basis to oversee the physical actions on the site. The Task Force was a multi-disciplinary committee consisting of TI personnel from: Environmental Engineering, Health and Safety, Facilities, Transportation, Purchasing, Security, and Human Resources. The committee also included representatives from the two primary contractors on the site: Creative Pollution Solutions (CPS) and Franklin Environmental Services (FES). This task force assisted in making all decisions involving health and safety, remediation, human relations, waste disposal, transportation, and security.

**TEXAS INSTRUMENTS INCORPORATED
FINAL REPORT: REMEDIATION OF THE FORMER
RADIOACTIVE WASTE BURIAL SITE**

License: SNM-23
Docket No: 70-33

Date: September 1993
Version: 1.0

3.2 Project Organization

TI contracted with two companies to perform the majority of the work on site. CPS was contracted for the radiological support for site operations. This included advising TI on areas requiring excavation as well as providing radiological health and safety support on site. FES was contracted for the excavation portion of the site work. In addition, FES provided all non-radiological health and safety support. Two other contractors for TI, Bartlett Nuclear and Guild Drilling, were asked to work under the supervision of CPS. The oversight of all site operations was the responsibility of TI. Figure 3.1 shows an organizational chart for the project.

During the backfill and restoration of the site, TI contracted with four additional contractors to perform backfilling of the excavated area, asphalt paving of the parking lot, restoration landscaping, and topographic surveying of the excavated area. The contractors used for these operations were Walsh Construction, Narrangansett Improvement, Old Farm Nurseries, and E. Otis Dyer, respectively.

4.0 REMEDIATION ACTIVITIES

4.1 Remediation Criteria

The purpose of the remediation of the burial area was to excavate contaminated soil to the extent necessary to achieve clean-up criteria prescribed in Option 1 of the BTP. For processed uranium (uranium without daughter products) the criteria for surface contamination or contamination of soil in areas without use restriction are 35 pCi/g for depleted uranium and 30 pCi/g for enriched uranium. The acceptable exposure rate at one meter above the surface as determined by the NRC is 10 μ R/h above background or 21 μ R/h total for this location (i.e., approximately 2 times background). This goal was to be achieved by using the approach outlined in the "Remediation Plan" in Appendix J.

**TEXAS INSTRUMENTS INCORPORATED
FINAL REPORT: REMEDIATION OF THE FORMER
RADIOACTIVE WASTE BURIAL SITE**

**License: SNM-23
Docket No: 70-33**

**Date: September 1993
Version: 1.0**

4.2 Contaminants Identified

The primary contaminants of interest for the remediation of the burial area were: U-234, U-235 and U-238. Prior to remediation of the site, surveys indicated that the contaminated soil concentrations in the burial area were believed to be slightly greater than the Option 1 criteria of 30 pCi/g total uranium. There was some indication that some of the metal debris in the burial area was contaminated to a greater extent than the soil.

While a few areas were found to have elevated levels of Thorium-232 it was determined that elevated thorium levels were associated with elevated uranium levels. Remediation controlled on the basis of uranium exclusively, resulted in a proportional reduction of thorium to below its acceptable levels and therefore thorium was not of significant concern. For this reason the focus of the remediation was on the level of total uranium activity in soil.

4.3 Previous Radiological Surveys

Previous radiological surveys included surveys performed by TI, ORAU, and CPS. These surveys were performed between 1982 and 1992. The surveys were used to determine the extent and depth of contamination within the burial area. These surveys indicated that the major area

of contamination was between 160N - 190N x 110E - 140E. Some of the initial survey data provided by ORAU indicated that isolated debris might be more of a problem than the surrounding soils.

4.4 Chronology of Site Operations

This section outlines the chronology of site operations involved in the remediation of the former radioactive waste burial site at TI. The operations described below took place between July 1992 and September 1993. Figure 4.1 shows a timeline of the entire process.

**TEXAS INSTRUMENTS INCORPORATED
FINAL REPORT: REMEDIATION OF THE FORMER
RADIOACTIVE WASTE BURIAL SITE**

License: SNM-23
Docket No: 70-33

Date: September 1993
Version: 1.0

4.4.1 Pilot Study

In July, 1992 TI retained CPS to perform a pilot study to better determine the extent of the contaminants within the burial area. A series of parallel trenches were excavated. The trenches were approximately 30 meters long and 2-3 feet deep. Composite samples were taken from the trenches.

Soil samples were analyzed using a gross alpha screening method to allow for rapid field assessment of the contaminants (see Appendix C). Four composite samples were sent to a certified laboratory for analysis by both alpha and gamma spectroscopy. A correlation was established between the gross alpha screening method and the alpha spectroscopy data. The gross alpha screening was also shown to have very good correlation with gamma spectroscopy data (see Appendix C). Once characterized, isotopic information was no longer necessary for comparison with the total uranium criteria. The results of the pilot survey can be found in Appendix G.

During the pilot study, the health and safety requirements of the site included: level C protection (full face respirators and tyvek suits) within the exclusion zone (see Figure 4.2), Breathing Zone Air (BZA) sampling, personal Thermoluminescent Dosimeters (TLDs), and Area Air (AA) sampling. This level of protection was selected as a conservative measure. For the actual remediation of the site, the level of protection was downgraded to level D (no respiratory protection).

The pilot study successfully identified one highly elevated sample. This sample was obtained at a depth of approximately 4-5 feet. One conclusion from the pilot excavation was that the contaminants may have been deeper than initially expected.

4.4.2 Initial Remediation Estimates

Initial remediation estimates were provided based on the limited information available from the ORAU survey and the CPS pilot study. The remediation option report, as provided in Appendix H, presented several options ranging from further characterization to the removal of a limited number of elevated locations. In the most optimistic scenario, it was estimated that the remediation would generate approximately 6,000 ft³ of soil and debris for disposal. On the conservative side, the remediation options presented indicated volumes in excess of 30,400 ft³.

**TEXAS INSTRUMENTS INCORPORATED
FINAL REPORT: REMEDIATION OF THE FORMER
RADIOACTIVE WASTE BURIAL SITE**

License: SNM-23
Docket No: 70-33

Date: September 1993
Version: 1.0

After review of radiological characteristics, debris content, anticipated volumes, modes of transportation, and financial objectives, available disposal options were evaluated. Based on these criterion, the most viable disposal option was determined to be EnviroCare of Utah. This decision was facilitated by the sites ability to handle uranium contaminated materials and to receive bulk rail shipments.

Due to the large variation in the volume estimates additional subsurface sampling was performed to aid in the selection of the appropriate remediation option.

4.4.3 *Pre Excavation Survey*

With the identification of contamination at a depth greater than one meter, identified in the CPS pilot study, further selected split spoon samples were taken. The sampling protocol for this exercise was to sample the burial area to a greater depth and over a larger area than in the pilot study. This survey was designed in an attempt to bound the extent of the contamination.

This survey focused specific attention in the area of 160N - 190N x 110E - 140E due to the results of the CPS pilot study and the ORAU survey. Exclusive of this sampling, random samples were also collected within the larger defined burial area.

The results of this survey indicated contamination, at concentrations greater than 30 pCi/g of total uranium, was not limited to isolated locations. Based upon these results, revised estimates for remediation were generated.

4.4.4 *Revised Remediation Estimates*

After the pre-excavation survey CPS provided revised remediation estimates incorporating the additional subsurface sampling results. These estimates concluded that larger areas might require remediation.

**TEXAS INSTRUMENTS INCORPORATED
FINAL REPORT: REMEDIATION OF THE FORMER
RADIOACTIVE WASTE BURIAL SITE**

License: SNM-23
Docket No: 70-33

Date: September 1993
Version: 1.0

A remediation plan was developed to minimize total volumes. The remediation plan outlined a two phase approach. The first phase was to remediate isolated elevated locations. The second phase was to excavate remaining areas identified in the plan for removal of debris and disposition of materials. This plan (Appendix J) was submitted and approved by the NRC on August 26, 1992, as Amendment No. 16 to License No. SNM-23 (Appendix K).

4.4.5 Initial Excavation

The initial excavation of the burial area started on August 31, 1992. Initially, the excavation was performed using a small backhoe. Excavated materials were transferred directly to a front end loader for transport to a mechanical screener to separate potentially contaminated debris and aggregate from the soils. GM monitoring and alpha screening techniques were employed to determine extent of excavation and disposition of soils. The sampling method is included within Appendix C.

The excavation began at 170N x 130E, the location where the most elevated sample had been previously identified. The first day of excavation identified a large pocket of debris at a depth of approximately 4 - 6 feet. Some of the debris indicated surface readings with a pancake GM detector of greater than 20,000 counts per minute (cpm). The surrounding soil had concentrations ranging from 100 pCi/g to > 5000 pCi/g total uranium based on gross alpha screening results.

The debris consisted of laboratory bottles, graphite crucibles, extruded uranium/ zirconium tubes, mounted uranium samples, 55 gallon drums, partial mock fuel elements, metal fines, uranium ingots, ductwork, uranium/aluminum plates, etc. Some of the debris could be directly associated with contract work performed under the direction of the Schenectedy Naval Reactor Office.

Due to the volume of debris excavated, five specimens were assayed to determine isotopic enrichments. These specimens were determined to have either natural or depleted abundancies of U-235. This assay information was later used for determining activities for shipment and is provided in Appendix B, Attachment 3.

The volume of debris and levels of contamination were greater than anticipated. These findings dictated an adjustment in the approach to remediation.

**TEXAS INSTRUMENTS INCORPORATED
FINAL REPORT: REMEDIATION OF THE FORMER
RADIOACTIVE WASTE BURIAL SITE**

License: SNM-23
Docket No: 70-33

Date: September 1993
Version: 1.0

4.4.6 *Adjustment in approach to remediation*

Since the levels of soil contamination and debris were higher than expected, an adjustment in the remediation approach was implemented. This adjustment would allow for the separation of highly contaminated soil / debris from soils with moderate levels of contamination (between 30 pCi/g and 500 pCi/g), and soils which may be suitable for backfill.

As of September 10, 1992, the total volume of contaminated soil / debris staged for disposal was approximately 10,000 ft³. The excavation continued on the south side of the burial area at 160N - 165N x 135E - 150E. It appeared that a trench of contaminated material exhibiting elevated levels of radioactivity, easily identifiable by both radiation levels and a characteristic dark gray color, cut diagonally through these grid points. This trench was at a depth of approximately 4 to 6 feet. In many areas the contaminated soils extended approximately 1 to 2 feet below existing groundwater elevations.

Field observations indicated that the contamination did not extend far below the ground water levels. Since the volume of wet soils was relatively small, and pumping to locations outside the excavation presented regulatory obstacles, no mechanical dewatering was performed. Rather, the wet soils were staged and allowed to drain back into the excavation prior to further processing.

As the excavation proceeded the increased volumes mandated a change in the methods for processing and staging soils. On September 15, 1992 larger excavation equipment was brought on site in order to remove identified volumes more efficiently. An additional mechanical screener was brought on site to facilitate soil processing. Rather than attempting to stage all soils in roll-off containers, soils were staged in piles within the exclusion zone. Wet soils were staged near the excavated area as previously discussed. Even after air drying some of the wet soils required stabilization prior to ultimate disposition.

Shipment of contaminated soils for disposal to EnviroCare of Utah began in early October of 1992. The higher activity soil / debris was packaged in B-25 boxes and loaded on rail cars for shipment. The remaining soils were acceptable in bulk load form and therefore were loaded directly in rail cars for shipment (See Appendix B).

**TEXAS INSTRUMENTS INCORPORATED
FINAL REPORT: REMEDIATION OF THE FORMER
RADIOACTIVE WASTE BURIAL SITE**

License: SNM-23
Docket No: 70-33

Date: September 1993
Version: 1.0

On September 26, 1992, the excavation of the north side of the burial area was initiated. The remediation approach was modified by first excavating the top 1 to 2 feet of soil, which was usually determined to be below BTP Option 1 criteria, then excavating the remaining area to acceptable levels. Samples were taken from the floor of the excavation, prior to the infiltration of ground water and rain water into the area. These samples were used as part of a site survey subsequently submitted to the NRC. This survey is included in Appendix E.

On November 28, 1992, TI submitted a survey of the burial area to the NRC. This survey consisted of alpha screening results for soil samples from the floor of the excavated area and a gamma exposure rate walkover survey for the remaining areas within the defined burial area. Figure 4.3 shows the extent of the excavated area at this point.

4.4.7 Initial NRC / ORISE Site Visit

The NRC and ORISE arrived at TI on December 15, 1992, to perform a verification survey of the burial area. ORISE performed a gamma exposure rate walkover survey in the burial area and along the bounds of the excavated area. With the assistance of CPS, ORISE took a limited number of soil samples from the floor of the excavation (through several feet of standing water) and from the overburden piles. At the time of the site visit, the NRC raised concerns with levels found on some walls of the excavation. NRC recommended that the bounds of the excavation be extended in certain areas and that the extent of the excavation be verified.

4.4.8 Extending the Bounds of the Excavation

From December 15, 1992 to January 5, 1993, the bounds of the excavation were extended in accordance with the NRC recommendations. The bounds of the excavation were extended in locations where the NaI readings, on the accessible portion of the wall, were greater than two times background. Subsurface split spoon soil samples were taken to demonstrate that the excavation had been appropriately extended. As shown in Figure 4.4, the excavation extended beyond the original exclusion zone and into the building 11 parking lot.

**TEXAS INSTRUMENTS INCORPORATED
FINAL REPORT: REMEDIATION OF THE FORMER
RADIOACTIVE WASTE BURIAL SITE**

License: SNM-23
Docket No: 70-33

Date: September 1993
Version: 1.0

The excavation in this area was in close proximity to a 12 inch water main providing the only service for fire protection and all other uses within two buildings. In order to prevent freezing or physical damage to the exposed water main, this area was immediately backfilled after removal of contaminated soils and confirmatory sampling. Prior to the backfilling, TI notified the NRC of its intent and obtained their concurrence.

On January 8 1993, a revised final survey report was submitted to the NRC.

4.4.9 *Scraping the Floor of the Excavation*

The NRC reviewed the TI "Revised Final Survey Report", dated January 8, 1993 along with the ORISE verification survey results of December 15, 1992, and recommended that TI address two elevated locations on the floor of the excavated area. To address these locations it was necessary to dewater the excavated area.

Dewatering involved pumping the water out of the excavated area, filtering the water and discharging the effluent. Discussions between TI and the NRC concerning the dewatering operation concluded that this operation, and its subsequent discharge, was consistent with the existing requirements of TI's license. In order to meet Environmental Protection Agency (EPA) requirements, TI obtained a National Pollution Discharge Elimination System (NPDES) permit exclusion for the discharge of the effluent. Approval from the EPA was received on May 3, 1993. Discussion of radiological aspects of the water pumped and site hydrogeology is found in Appendix F.

The pumping process began on May 14, 1993. Since there was continuous groundwater infiltration, the floor of the excavation was never completely dry however, continuous pumping allowed for access with excavation equipment. Pumping was concluded on June 9, 1993.

CPS performed a walkover survey within the excavated area to identify any areas greater than two times background on the NaI survey meter. In addition to the two locations identified in the NRC inspection report, several other isolated locations were identified during this walkover. In most cases, these isolated locations were due to a small amount of debris and were remediated by hand digging. The two locations identified by the NRC required more extensive scraping

which was achieved through the use of conventional excavation equipment. The scraping in these regions involved excavation to depths ranging from 2 to 12 inches.

**TEXAS INSTRUMENTS INCORPORATED
FINAL REPORT: REMEDIATION OF THE FORMER
RADIOACTIVE WASTE BURIAL SITE**

License: SNM-23
Docket No: 70-33

Date: September 1993
Version: 1.0

4.4.10 *NRC survey*

On June 2, 1993, the NRC conducted a site inspection. During the inspection the NRC performed a walkover survey within the excavated area. All areas within the excavated area were determined to be between 1 and 1.5 times background (using NaI survey meter) except for two locations (185N x 157E and 177.5N x 122E) which showed levels of 3 times background. These locations were remediated during the day of the NRC survey.

The NRC also performed a walkover with a Micro-R meter within the excavated area. The exposure rates at one meter above the floor of the excavation ranged from 11 μ R/hr to 15 μ R/hr.

The NRC obtained four soil samples from the areas scraped. The concentrations of these samples ranged from 16 pCi/g to 58 pCi/g based on gross alpha screening.

4.4.11 *Topographical Survey*

On June 3, 1993, prior to the backfilling operation, TI retained the services of E. Otis Dyer, a Registered Professional Engineer and Land Surveyor, to develop a topographical map of the excavation area and its environs. This map recorded the horizontal and vertical extent of the excavation at the point in time when all field work ceased as the project objectives had been achieved. This map is provided as a size "D" print located at the end of this report.

4.4.12 *Backfilling*

After the NRC inspection was complete, backfilling of the excavated area began. The overburden piles were used as backfill material. During the backfill operation CPS conducted quality assurance walkover surveys.

**TEXAS INSTRUMENTS INCORPORATED
FINAL REPORT: REMEDIATION OF THE FORMER
RADIOACTIVE WASTE BURIAL SITE**

License: SNM-23
Docket No: 70-33

Date: September 1993
Version: 1.0

5.0 FINAL SURVEY

5.1 Introduction

The final survey was conducted to demonstrate that the criteria outlined in Option 1 of the BTP was achieved. It included three main components: split spoon samples taken around the perimeter of the excavated area, soil samples collected from the floor of the excavation, and a walkover survey which assessed exposure rates. These surveys were performed in accordance with the remediation plan.

This final survey report includes data collected during the post excavation survey report (November 28, 1992), the revised final survey (January 8, 1993), data collected after the final scraping of the floor of the area (June 3, 1993), and final walkover results after backfilling was completed in late June 1993. A description of the methodology and results from these surveys are included in Appendix E. A summary of the findings is included below.

5.2 Perimeter Split Spoon Sampling

The perimeter split spoon sampling demonstrated that the excavation addressed the appropriate areas. The split spoon sample locations are shown in Figure 5.1. The average concentration over the total depth of each borehole (0 to 6 feet) ranged from 7.0 to 27.7 pCi/g. The concentrations of individual split spoon samples ranged from 4 pCi/g to 37 pCi/g. These results are tabulated in Appendix E.

5.3 Surface soil sampling within the excavated area

Surface soil sampling of the floor of the excavation consisted of samples at each corner, and in the middle of each 10 meter x 10 meter grid cell. These locations are shown in Figure 5.2. The concentrations of the soil samples ranged from 4 pCi/g to 55 pCi/g. The 10 meter x 10 meter grid cell averages, within the excavated area, ranged from 18.2 pCi/g to 31.6 pCi/g. While two grid cells averaged slightly over the 30 pCi/g criteria, these averages are conservative by virtue of the analytical technique. As demonstrated in the alpha screening correlation in Appendix C and ORISE's independent analysis of split samples taken during the initial NRC / ORISE site visit, alpha screening results at concentrations less than 20 pCi/g are conservative. This conservatism is documented in correspondence between ORISE and NRC of January 25, 1993 included in Appendix K. Details of the surface soil sampling results are tabulated in Appendix E.

**TEXAS INSTRUMENTS INCORPORATED
FINAL REPORT: REMEDIATION OF THE FORMER
RADIOACTIVE WASTE BURIAL SITE**

License: SNM-23
Docket No: 70-33

Date: September 1993
Version: 1.0

5.4 Walkover surveys of the Burial Area

After the backfilling operation was completed, and prior to landscaping, CPS conducted an extensive walkover survey of the burial area. Results of a near surface walkover survey, using a NaI survey meter, identified four locations in excess of one and one half times background. No areas were identified greater than two times background. Results of the one meter survey, at all 10 meter x 10 meter grid locations within the burial area, indicated results between one and one and one half times background. The results of these surveys are further discussed in Appendix E.

6.0 CONCLUSIONS

Between July 1992 and July 1993, the former radioactive waste burial site at TI was successfully remediated. The final volume of soil and debris requiring disposal was approximately 63,000 cubic feet. Radiological surveys conducted between November 1992 and July 1993 demonstrate that the remediation efforts were effective in reducing residual activity within the burial site to meet NRC Option 1 BTP criteria for release.

Figure 2.1
 Map of Massachusetts and Attleboro Showing Location and Plan View of the
 Texas Instruments Site.






Figure 2.2
Defined Burial Area



| REVISIONS | | | | CREATIVE POLLUTION SOLUTIONS, INC. | |
|-----------|------|-------------|----|------------------------------------|------|
| NO. | DATE | DESCRIPTION | BY | CHKD. | DATE |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |

| | |
|--|-----|
| CREATIVE POLLUTION SOLUTIONS, INC. | |
| TEXAS INSTRUMENTS & ATTACHEMOS BURIAL SITE PROJECT | |
| DATE | BY |
| 10/10/00 | NTS |

Figure 2.3
Burial Area with Grid Layout




Figure 2.4 Pilot Survey Site Layout




Figure 3.1
Organizational Chart




Figure 4.1
 Schedule for Texas Instruments Incorporated Soil Remediation




Figure 4.2
Control Zone Layout




Figure 4.3
Extent of Excavation as of November 28, 1992.




Figure 4.4
Final Site Excavation




Figure 5.1
Split Spoon Sample Locations





Figure 5.2
Location of Samples from the Floor of Excavated Area



Appendix C

Radiological Field Screening for Uranium in Soil

RADIOLOGICAL FIELD SCREENING TECHNIQUES FOR URANIUM IN SOIL

1.0 INTRODUCTION

For the determination of uranium concentrations in soil two methods are commonly employed: gamma spectroscopy and alpha spectroscopy.

The use of alpha spectroscopy for the determination of total uranium in soil involves the chemical separation of the uranium from the soil and the direct measurement of the alpha particles associated with each radionuclide: U-235, U-234, and U-238.

The use of gamma spectroscopy for the determination of total uranium involves determination of U-235 concentration directly, although radium (186 keV) can cause some interference, and by inference and/or scaling factors, the concentrations of Uranium-238 and Uranium-234 respectively. The scaling factors for the estimation of the U-234 concentrations are often based upon a U-234 to U-235 ratio. Industry experiences have generally found a ratio of 22 to be representative. This scaling factor, however, may vary significantly depending upon previous site specific activities. It is therefore more reasonable to base the isotopic uranium distribution on alpha spectroscopy data obtained from representative samples on site.

The analytical results of the samples provided herein indicated a scaling factor disparate from industry norm in representing a value of approximately 11 - 13 for the ratio of U-234 to U-235. This discrepancy could be related to either the use of natural and depleted uranium in the early fabrication and experimentation prior to the production of products requiring enriched uranium or earlier naval fuel activities where reprocessed uranium may have been introduced thereby generated different isotopic ratios.

Regardless, routine use of gamma spectroscopy and alpha spectroscopy is time consuming, requires extensive experience, sample preparation, analysis and interpretation, and requires the use of independent laboratories or extensive capital outlay. It was therefore desirable to develop methodologies which could be used in the field to assess the extent of remediation activities and to provide a reasonable and accurate estimation of contaminants (uranium) for final determinations.

Two such methodologies are presented: GM screening and gross alpha screening. GM screening uses a pancake type GM probes placed in close proximity to the soil matrix of interest. It has been determined from experimentation and practice that this technique is limited to concentration values in excess of 100 pCi/g uranium in soil. Nonetheless this does not detract from its utility within field application during physical excavation. Gross Alpha Screening provides for estimation of total uranium activity at levels well below the action limits specified for remediation. This appendix presents the basis for the use of GM and gross alpha screening techniques.

2.0 GM SCREENING TECHNIQUE.

A technique for the use of a hand held GM survey meter is desirable for quick determinations of remediation attainment. With the emission of alpha, beta and gamma radiations from uranium and its' progeny, the use of a GM detector becomes a desirable option for gross screening of materials for contamination in levels which exceed natural abundances.

To quantify levels and extent of contamination in the TI soil which can be identified by a conventional hand held GM survey meter, a simple response determination was done. One composite sample analyzed by LAL and determined to contain 4700 pCi/gram of uranium, was prepared in an infinitely thick geometry for the detection of beta. The thickness of soil required to obtain "infinitely thick" was based on a Sargents Rule calculation for beta energies over 0.8 MeV.

SARGENTS RULE

$$E > 0.8 \text{ Mev}$$

$$R = 0.526 E^{-0.094}$$

Where R is the range in grams/cm²

$$R = 0.526 (2.3)^{-0.094}$$

$$R = 0.486 \text{ grams/cm}^2$$

for a soil density of 2.0 grams/cm³


$$R = 0.243 \text{ cm or } 0.618 \text{ inches}$$

A GM detector was placed in direct contact with the soil of known uranium content, 4700 pCi/gm, and the detector response was recorded. A single sheet of mylar was used to prevent detector contamination. To establish the condition of equilibrium detector response the sample volume (thickness) was incrementally reduced while recording the detector response. The results of this exercise are plotted and provided in Figure C-1.

The uniformity in the GM detector response at sample down to thicknesses of only a few centimeters indicates the ability to achieve equilibrium conditions within a sample volume of 100 cm³ (50 grams). Based on the detector surface area and the sample volume at which non equilibrium conditions were observed, the approximate range or thickness of soil in this sample, necessary to achieve equilibrium conditions, was experimentally determined to be less than 1.0 centimeters. This experimental conclusion is consistent with the theoretical calculation shown above.

Figure C-1
Analysis of GM Detector Response to Varying Soil Mass

| | | | | | | | | | | | | |
|-------------------|----|------|------|------|------|------|------|------|------|------|------|------|
| Mass of Soil | 0 | 15 | 20 | 30 | 50 | 100 | 150 | 200 | 250 | 300 | 350 | 400 |
| Detector Response | 40 | 3400 | 3800 | 4200 | 4500 | 4400 | 4400 | 4500 | 4500 | 4500 | 4500 | 4500 |



Using the known sample concentration of 4700 pCi/gm (LAL); an approximate effective sample volume (based on the detector window area); and the experimentally determined effective range; the resulting mass of soil is calculated at approximately 20 grams. The sample concentration, 4700 pCi/gram, multiplied by the sample mass of 20 grams provides the total effective sample activity of 9.4E4 pCi or 2.08E5 disintegrations per minute (dpm). With the detector response of 4500 counts per minute (cpm) the effective detector efficiency is calculated.

$$4500 \text{ cpm} / 2.08E5 \text{ dpm} = 2.15E-2 \text{ c/d}$$

or

An effective GM detector efficiency of 2.15%

This demonstrates the sensitivity of the GM to small sample volumes and low concentrations. If a criteria of 2 times background is applied as a field screening action point an effective sample concentration can be calculated.

$$\text{GM background} = 50 \text{ cpm}$$

$$2 \times 50 \text{ cpm} = 100 \text{ cpm or } 50 \text{ cpm net}$$

$$50 \text{ cpm(net)} / 0.0215 \text{ cpm/dpm} = 2.32E3 \text{ dpm}$$

applying an effective sample mass of 20 grams

$$1.05E3 \text{ pCi} / 20 \text{ grams} = 52.4 \text{ pCi/gram}$$

If the conservative assumption is made that the gross GM screening could effectively see contamination in excess of twice background then the application of "no detectable" would result in a contamination level of 52 pCi/gm. Therefore, results at or below twice background could be instituted as a technique for determining when to suspend remediation and apply the more sensitive technique like alpha screening to determine actual contamination levels. This screening technique will eliminate excessive delays in the determination of the extent to which each location should be mitigated. The cost savings in laboratory sample analysis alone justifies the use of such a technique not to mention the costs associated with delays in site excavation.

3.0 GROSS ALPHA SCREENING TECHNIQUE.

3.1 Introduction.

The gross alpha screening technique used during the excavation involved direct counting of alpha particles within a soil matrix. The use of direct counting of alpha particle for the detection of radiological constituents mixed within a sample matrix has been discounted as a viable technique mainly due to the concerns over self absorption of the alpha particle within the sample matrix itself. The common industry method of quantifying alpha activity, alpha spectroscopy, involves

minimizing any self absorption by means of chemical preparation such as ion exchange or microwave dissolution of a sample aliquot and subsequent plating onto a surface in an infinitely thin layer. The sample is then evaluated in a similar manner as in gamma spectroscopy where the detection of the radiation within the detector results in proportional counts to appear on the channels of the analyzer. The resolution and peak fitting difficulties with this technique requires careful and precise analytical preparation as well as detailed calibration. Even when these factors are adequately addressed sample count times can be very long. The cost of alpha spectrographic analysis can be on the order of \$200 to \$500 per sample with turn around times ranging from 7 to 60 days.

The desire to quantify alpha emitting nuclide concentrations such as uranium and plutonium within various environmental media because of there extensive uses over the past forty plus years has brought on the need to further evaluate a direct, quick and inexpensive technique for the quantification of alpha emitters.

One such technique was developed from the work published by K.W. Skrable and K.A. Pheonix in Health Physics, Volume 60, Number 3, March 1991 "Theoretical Response of a ZnS(Ag) Scintillation Detector to Alpha emitting Sources and Suggested Applications". This approach derives an expected count rate from an infinitely thick source of alpha emitting material using Zeigler's theoretical ranges of alpha particle based on energy and the elemental make up of the sample matrix. Early trials of this technique indicated a correlation between the gross alpha counts and the isotopic alpha concentrations determined by alpha spectroscopy.

The expected results (pCi/gm), however, did not yield the values determined by alpha spectroscopy. With the strong correlation of the total alpha counts to the alpha (uranium) concentration determined by the certified lab a cross calibration using a range of samples was pursued. In addition, field portable counting systems and standard sample collection and preparation techniques had to be developed.

3.2 Sample Counting Equipment.

The theory of counting alphas with a phosphor such as ZnS(Ag) is to have intimate contact between the alpha emitting material and the phosphor. This was achieved by using 2 inch disks of ZnS(Ag) on the bottom (phosphor side up) of a 2 inch clear plastic culture dish. The soils could then be placed within the dish directly on top of the phosphor disk. The dish with the soil phosphor sandwich is then placed on a conventional photo multiplier tube (pmt). The PMT is housed inside a light tight container with a removable lid.

One tremendous advantage to this PMT arrangement is that the detector background count rate is very near zero for the intended count time of 10 minutes. Typical count rates have been 0.01 to 0.05 counts per minute over extended count times.

3.3 Sample Preparation.

With the sample in a fixed configuration within the dish the only other factors which need to be standardized were (1) the water content of the soil and (2) the particle size of the soil.

The easiest approach to standardizing the moisture content of the soil samples which may be experienced in the field for counting was to dry them in a small oven to eliminate the moisture inconsistencies. A simple set of experiments was undertaken to determine what combination of temperature and drying time was optimum. It was experimentally determined that a 15 to 20 gram samples of soil with varying moisture contents could be heated in the oven within a small tin dish for 15 minutes at 100 degrees centigrade and result in consistent moisture removal on soils typically found insitu.

The particle size of the soil was important to insure the most intimate contact between soil and phosphor was achieved. Experiments sieving dried soils were done to evaluate the effects of sieve size to the sample counts. It was obvious that all aggregate such as small rocks should be removed as they would preclude the soils from touching the ZnS(Ag). Various sieves were used to determine an acceptable sieve size to maximize counter response. It was determined that once below a sieve size of about 0.125 inches consistent response on the detector is achieved. Based on this determination the use of a common kitchen strainer (sieve size about 0.0625 inches) was employed.

3.4 Sample Counting and System Evaluation.

In addition to standard chi-square tests of the counter to determine the reliability and stability of the counting system daily source checks and background checks were performed. Routine samples were also split and run as well as independent splits using gamma spectroscopy and alpha spectroscopy. Information relating to individual sample counts on a single sample was desirable to insure reproducibility of the results for a single sample. A prepared dish, phosphor and soil configuration was repeatedly put onto the counter, counted and taken off. This procedure was followed for ten iterations and the results are tabulated in Table C-1. The results show that the system experienced a smaller sample deviation than theoretically expected.

With a background count rate at or near zero, the calculation of an MDA is simplified. Assuming a background of zero the MDA would be 2.7 pCi/g. However, "background" soil, free of any alpha emitters other than those provided by nature would present additional counts and therefore a different MDA. These background counts would not only arise from the three Uraniums of interest but any other natural occurring alpha emitting species and therefore confounds the interpretation of low count samples. The results of alpha screening on background soils yielded 10 counts per ten minutes. Alpha spectroscopy correlated this sample to approximately 2.5 pCi/g of total uranium. Therefore any sample with a count of less than this, could be interpreted as background soil at 2.5 pCi/g. Nonetheless, the ability to determine soil concentrations at less than 30 pCi/g is established.

TABLE C-1

| REPETITIVE COUNTS ON SINGLE SAMPLE | |
|--|----|
| Test #1 High Sample Activity | |
| (COUNTS PER 10 MINUTES) | |
| | 90 |
| | 97 |
| | 99 |
| | 88 |
| | 89 |
| | 95 |
| | 92 |
| | 90 |
| | 99 |
| | 90 |
| MEAN = 92.90 | |
| EXPERIMENTAL STANDARD DEVIATION = 4.23 | |
| THEORETICAL STANDARD DEVIATION = 9.64 | |

| REPETITIVE COUNTS ON SINGLE SAMPLE | |
|--|----|
| Test #2 Low Sample Activity | |
| (COUNTS PER 10 MINUTES) | |
| | 23 |
| | 24 |
| | 16 |
| | 23 |
| | 17 |
| | 20 |
| | 16 |
| | 22 |
| | 22 |
| | 21 |
| MEAN = 20.40 | |
| EXPERIMENTAL STANDARD DEVIATION = 3.03 | |
| THEORETICAL STANDARD DEVIATION = 4.52 | |

TABLE C-2

| INDEPENDENT PROGENY COUNTS FROM PARENT SAMPLE | |
|---|----|
| Test #1 High Sample Activity (RS 414) | |
| (Each Individual Sample Counted 10 Minutes) | |
| | 97 |
| | 88 |
| | 90 |
| | 95 |
| | 99 |
| | 92 |
| | 90 |
| | 99 |
| | 90 |
| | 99 |
| MEAN = 93.90 | |
| EXPERIMENTAL STANDARD DEVIATION = 4.38 | |
| THEORETICAL STANDARD DEVIATION = 9.69 | |

| INDEPENDENT PROGENY COUNTS FROM PARENT SAMPLE | |
|---|----|
| Test #2 Low Sample Activity (MP 5) | |
| (Each Individual Sample Counted 10 Minutes) | |
| | 23 |
| | 26 |
| | 22 |
| | 18 |
| | 21 |
| | 18 |
| | 20 |
| | 20 |
| | 23 |
| | 15 |
| MEAN = 20.6 | |
| EXPERIMENTAL STANDARD DEVIATION = 3.12 | |
| THEORETICAL STANDARD DEVIATION = 4.54 | |

TABLE C-3

| INDIVIDUAL PROGENY SAMPLES FROM PROCESS PILE | |
|---|----|
| Ten Samples Cored At Random From Reed Screened Process Pile | |
| Reed Screened Process Pile Volume: 200 Cubic Feet | |
| Each Individual Sample (10 - 20 grams) Counted 10 Minutes | |
| RS 277 - 1 | 47 |
| RS 277 - 2 | 62 |
| RS 277 - 3 | 37 |
| RS 277 - 4 | 49 |
| RS 277 - 5 | 61 |
| RS 277 - 6 | 40 |
| RS 277 - 7 | 70 |
| RS 277 - 8 | 55 |
| RS 277 - 9 | 87 |
| RS 277 - 10 | 52 |
| MEAN = 56.00 | |
| EXPERIMENTAL STANDARD DEVIATION = 14.84 | |
| THEORETICAL STANDARD DEVIATION = 7.48 | |

3.5 Sample Variability.

Due to the small sample volume needed with this technique an evaluation of sample variability was prudent. In the field a one liter sample is extracted under standard protocols. From two such sample volumes of different activity concentrations multiple counting samples were prepared. The tabulation of these repetitive counts and the resulting statistics are provided in Table C-2. This data set also shows the statistics which complement this technique. The actual observed deviation about the mean is less than expected by theoretical calculation.

3.6 Sample Collection In The Field.

The process of soil excavation followed by reed screening for the removal of aggregate and contaminated debris resulted in the continuous generation of piles of screened soils. These piles were estimated at 200 cubic feet each and were staged separate for each reed screen load. These piles were analyzed by alpha screening to determine their disposition. To insure adequate sampling as many as ten coring were taken in each pile. The individual coring were composited and homogenized within a larger container. From this composite a one liter aliquot is drawn for analysis. In support of this sampling procedure each individual coring has been analyzed for selected piles and the individual counts with the resulting statistics are provided in Table C-3. In this case of random sampling from a large volume of soil the resulting deviation about the sample mean is larger that expected by theoretical calculation. In almost all cases where samples were taken a one liter composite sample was taken, mixed and an aliquot sample of 20 grams, from the larger initial sample, taken for alpha screening.

3.7 Initial Alpha Screening Correlation.

The initial sampling done prior to the excavation of soils for disposal provided for the analysis of five unique samples by a certified laboratory. The samples were analyzed by gamma spectroscopy and plotted against alpha screening (Figure C-2) and analyzed by alpha spectroscopy and plotted against alpha screening (Figure C-3). The combined data is plotted in Figure C-4. From this data plot the relationship between alpha screening counts observed in a 10 minute count and the laboratory alpha spectrographic results was determined to be a stronger correlation. The gamma spectrographic results which, due to it's inherent difficulty in resolving low yield gamma peaks from progeny of the isotopes of primary interest, has less of an observable correlation. These plots also raise concerns over the use of gamma spectroscopy for the detection of low yield, low activity, progeny born photons in the determination of their parent activities. It is from these plots that the verification and justification of the alpha screening technique as a fast, cheap and reliable measurement method was based.

FIGURE C-2

| TOTAL URANIUM COMPARISON | |
|----------------------------------|--------------------------|
| Alpha Screening (counts/10 Min.) | LAL Gamma Spec. (pCi/gm) |
| 135 | 211.51 |
| 94 | 115.87 |
| 54 | 109.46 |
| 17 | 19.41 |
| 10 | 2.95 |




FIGURE C-3

| TOTAL URANIUM COMPARISON | |
|----------------------------------|--------------------------|
| Alpha Screening (counts/10 Min.) | LAL Alpha Spec. (pCi/gm) |
| 135 | 166.9 |
| 94 | 121.17 |
| 54 | 77.37 |
| 17 | 17.86 |
| 10 | 2.13 |





FIGURE C-4

| ALPHA SCREENING CORRELATION WITH URANIUM IN SOIL | | | |
|--|------------------|------------------|---------------------|
| LOCATION | LAL ALPHA SPEC. | LAL GAMMA SPEC. | CPS ALPHA SCREENING |
| | Total U (pCi/gm) | Total U (pCi/gm) | Total U (pCi/gm) |
| 240Nx180E(t) | 2.13 | 2.95 | 10 |
| 175Nx130E | 17.96 | 19.41 | 17 |
| 165Nx185E | 77.37 | 96.91 | 54 |
| 182.5Nx150E(t) | 121.17 | 109.46 | 94 |
| 165Nx122.5E | 166.9 | 211.51 | 135 |



3.8 Additional Alpha Screening Correlations.


The quality control and quality assurance aspects of the sampling and analysis program provided for further split sample opportunities. The ten ORISE ESSAP samples taken during a survey exercise were split with: (1) B&W Nuclear Environmental Services, Inc.; (2) EcoTek; (3) Lockheed Analytical Laboratory and (4) CPS, Inc. All samples except CPS, Inc. were analyzed by gamma spectroscopy. The comparison of this data is presented in Figure C-5. It is apparent that there is variability between sample results, however, these variations do not appear to be of a magnitude that is of concern or deviates from expected variations in sample results normally encountered with gamma spectroscopy for uranium-238 and uranium-235 and uranium-234 by inference from uranium-235.

4.0 CONCLUSIONS.

The use of gross counting of alpha emissions from infinitely thick sources of soil has proven through correlation to both alpha spectroscopy and gamma spectroscopy to be a viable method for the rapid, inexpensive and economical determination of soil activities. It provided for precise and cost effective mitigation of uranium contaminated soils and resulted in no loss time in waiting for results of samples taken. The cost savings just in sample analysis alone justifies its usefulness. With over 2000 samples analyzed by alpha screening a cost saving can be estimated to be in the order of \$500,000.00 (based on \$300.00 per sample by alpha spectroscopy). The ability to know sample results within tens of minutes resulted in the tight control in the disposition of soil volumes. This control provided unprecedented minimization of soils requiring ultimate disposal as radioactive waste, again saving hundreds of thousands of dollars.

FIGURE C-5

| COMPARISON OF TOTAL URANIUM ANALYSIS RESULTS | | | | | |
|--|--------------------------------------|-------|--------|-------|-----------------|
| Sample Locations | Total Uranium Concentration (pCi/gm) | | | | |
| | Gamma Spectroscopy | | | | Alpha Screening |
| | ESSAP | B&W | EcoTek | LAL | CPS |
| 134N x 118E | 5.3 | 4.65 | 16.5 | 5.44 | 12.8 |
| MP 4 | 9.6 | 21.82 | | 10.96 | 14.2 |
| MP 5 | 11 | 7.1 | 17.34 | 14.8 | 15.9 |
| 235N x 156E | 13 | 12.49 | | 8.62 | 19 |
| MP 1-2 | 15 | 11.65 | | 7.96 | 19.2 |
| 138N x 113E | 15 | 1.25 | 21.18 | 9.31 | 21.4 |
| Rock Pile | 26 | 26.96 | 25.12 | 17.24 | 25.8 |
| BFP 1 | 36 | 36.76 | | 29.4 | 29.9 |
| RS 410-411 | 75 | 56.99 | 49.86 | 51.11 | 75.3 |
| RS 414 | 77 | 90.77 | | 69.74 | 85 |



Appendix E

Final Survey Methods and Results

APPENDIX E: FINAL SURVEY METHODS AND RESULTS

Introduction

The final survey consisted of walk over near surface surveys and one-meter gamma surveys; floor soil samples from excavated area; and split spoon samples around the perimeter of the excavation. The walk over surveys were conducted to verify that exposure rates were below the acceptable levels outlined in the option 1 criteria of the NRC branch technical position. The excavation floor soil samples were taken in accordance with the remediation plan to assure that grid cell averages meet the 30 pCi/g limit established in the option 1 criteria. The split spoon samples were taken to verify the excavation area extended to the appropriate bounds.

Walk Over Survey

After the backfilling operation was completed, and prior final landscaping, CPS conducted an extensive walkover survey of the area previously defined as the burial area. This survey was conducted using a Ludlum model 3 survey meter with a Ludlum model 44-2 one inch x one inch sodium iodide scintillation detector. All readings for this portion of the survey were taken within two inches of the surface. Prior to the survey, the instrument background was determined to be about 2500 counts per minute. Radiation levels in the burial area were found to be between one and one and one-half times background except in four distinct locations. These areas are shown in Table 1 of this appendix. Of the areas greater than one and one-half times background all were less than two times background.

One-Meter Gamma Survey

In addition to the sodium iodide walkover survey a one meter gamma survey was conducted at appropriate grid intersections within the defined burial area. These measurements were performed using Ludlum model 3 survey meter with a Ludlum model 44-2 one inch x one inch sodium iodide scintillation detector. The response of the instrument is measured in counts per minute. Nominal background as determined in previous reports (ORAU, 1983) was between 10 - 11 $\mu\text{R/hr}$ (based on measurements with a pressurized ion chamber). This corresponds to a count rate on the sodium iodide detector of approximately 2500 cpm. According to Option 1 of the NRC branch technical position (BTP) an acceptable exposure level is 10 $\mu\text{R/hr}$ above background. In this case, 10 $\mu\text{R/hr}$ above background is equivalent to two times background. With this criteria, measurements equal to or less than two times background on the sodium iodide detector would meet the BTP criteria. In this one-meter gamma survey no areas were determined to have exposure rates greater than one and one-half times background. The results of this one-meter grid intersection survey are shown in Table 2 of this appendix.

Surface Soil Sampling

The soil sampling plan for the excavated area consisted of surface soil samples at each corner and in the middle of each 10 meter x 10 meter grid cell. Wherever possible surface (0-15cm) soil samples of approximately 1 kg each were collected at these points.

A map showing the sample locations is shown in Figure 1 of this appendix. Table 3 of this appendix shows the gross alpha screening results (in pCi/g total uranium) for the floor soil samples (see Appendix C for discussion of the gross alpha screening method). The average concentration for all samples taken from the floor of the excavation is 23.7 pCi/g. The minimum and maximum values are 4 and 55 pCi/g respectively. Table 4 shows the 10 meter x 10 meter grid cell averages. Two grid cells (170 - 180N x 110 - 120E, and 180 -190N x 150 - 160E) are slightly above the 30 pCi/g criteria however, when taking the average of those cells with adjacent cells the averages are 25.6 and 24.9 pCi/g respectively.

Split Spoon Sampling

Initially, the bounds of the excavation were surveyed to determine that the exposed surfaces (above the water level) were at background levels using a NaI meter. In areas where greater than background levels were found the excavation was extended. When all of the surfaces at the bounds of the excavation were determined to be at background levels, split spoon samples were taken as a means of demonstrating that the bounds of the excavation were at or below the approved guidance. The split spoon samples were taken around the perimeter of the excavated area to a depth of approximately six feet. These samples were taken approximately 1 to 5 meters back from the bounds of the excavation and approximately every 5 to 10 meters around the entire excavated area where practical. Sampling locations for the split spoon samples are shown in Figure 2 of this appendix. In locations where split spoon samples had been previously taken, the locations were not resampled and the previous data was used.

The soil samples which were collected during the split spoon sampling were analyzed using the gross alpha screening technique. The results show that the average concentration over the total depth of each borehole (approximately 0 - 6 feet) range from 7.0 to 27.7 pCi/g. These results demonstrate that the boundaries of the burial site had been reached. The results are shown in Table 5 of this appendix.

TABLE 1

WALKOVER SURVEY RESULTS OF AREAS GREATER THAN BACKGROUND

| <u>Location</u> | <u>Sodium Iodide Response (cpm)</u> |
|-----------------------------|---|
| 185 -190N x 170 -175E | 3000 - 4000* |
| 190 - 195N x 175 - 180E | 3000 - 4000 |
| 195 - 197.5N x 177.5 - 180E | 4000 |
| 182.5 - 185N x 180 - 182.5E | 4000 |

* Background levels were determined to be approximately 2500 counts per minute.

TABLE 2: ONE-METER EXPOSURE RATE MEASUREMENTS AT GRID INTERSECTIONS


| LOCATION | SURFACE (Nal reading in cpm)* | 1 METER (Nal reading in cpm)* |
|-----------------|--|--|
| 160N x 180E | 2800 | 2500 |
| 170N x 180E | 2450 | 2300 |
| 180N x 180E | 2250 | 2250 |
| 190N x 180E | 2250 | 2050 |
| 200N x 180E | 2200 | 2100 |
| 210N x 180E | 2150 | 2150 |
| 220N x 180E | 2100 | 2100 |
| 230N x 180E | 2200 | 2200 |
| 240N x 180E | 2250 | 2250 |
| 240N x 190E | 2400 | 2300 |
| 230N x 190E | 2400 | 2350 |
| 220N x 190E | 2450 | 2300 |
| 210N x 190E | 2500 | 2350 |
| 200N x 190E | 2250 | 2150 |
| 190N x 190E | 2200 | 2200 |
| 180N x 190E | 2000 | 2000 |
| 170N x 190E | 2500 | 2150 |
| 160N x 190E | 2500 | 2250 |
| 160N x 200E | 2750 | 2600 |
| 170N x 200E | 2350 | 2350 |
| 180N x 200E | 2200 | 2200 |
| 160N x 170E | 2450 | 2400 |
| 170N x 170E | 2400 | 2400 |
| 180N x 170E | 2650 | 2300 |
| 190N x 170E | 2250 | 2250 |
| 200N x 170E | 2100 | 2250 |
| 210N x 170E | 2150 | 2150 |
| 220N x 170E | 2150 | 2150 |
| 230N x 170E | 2150 | 2050 |
| 240N x 170E | 2200 | 2150 |
| 240N x 160E | 2250 | 2250 |
| 230N x 160E | 2450 | 2150 |
| 220N x 160E | 2150 | 2150 |
| 210N x 160E | 2200 | 2000 |
| 200N x 160E | 2300 | 2250 |
| 190N x 160E | 2050 | 2050 |
| 180N x 160E | 2100 | 2100 |
| 170N x 160E | 2700 | 2200 |
| 145N x 150E | 2450 | 2300 |
| 150N x 150E | 2300 | 2300 |
| 160N x 150E | 2300 | 2300 |
| 170N x 150E | 2300 | 2300 |
| 180N x 150E | 2000 | 1900 |
| 190N x 150E | 2100 | 2150 |
| 200N x 150E | 2050 | 2050 |
| 210N x 150E | 2150 | 2150 |

TABLE 2: ONE-METER EXPOSURE RATE MEASUREMENTS AT GRID INTERSECTIONS

| LOCATION | SURFACE (Nal reading in cpm)* | 1 METER (Nal reading in cpm)* |
|-------------|----------------------------------|----------------------------------|
| 220N x 150E | 2500 | 2300 |
| 230N x 150E | 2400 | 2250 |
| 145N x 140E | 2300 | 2200 |
| 150N x 140E | 2100 | 2200 |
| 160N x 140E | 2200 | 2100 |
| 170N x 140E | 2100 | 2100 |
| 180N x 140E | 2050 | 1900 |
| 190N x 140E | 2150 | 2100 |
| 200N x 140E | 2100 | 2150 |
| 210N x 140E | 2200 | 2250 |
| 220N x 140E | 2300 | 2400 |
| 145N x 130E | 2200 | 2200 |
| 150N x 130E | 2300 | 2200 |
| 160N x 130E | 2150 | 1950 |
| 170N x 130E | 1950 | 2000 |
| 180N x 130E | 2050 | 2050 |
| 190N x 130E | 2100 | 2050 |
| 200N x 130E | 2400 | 2150 |
| 210N x 130E | 2200 | 2200 |
| 220N x 130E | 2300 | 2200 |
| 220N x 120E | 2300 | 2200 |
| 210N x 120E | 2500 | 2200 |
| 200N x 120E | 2400 | 2300 |
| 190N x 120E | 2350 | 2350 |
| 180N x 120E | 2300 | 2100 |
| 170N x 120E | 2150 | 2150 |
| 160N x 120E | 2300 | 2100 |
| 150N x 120E | 2100 | 2150 |
| 140N x 120E | 2300 | 2150 |
| 140N x 110E | 2400 | 2400 |
| 150N x 110E | 2600 | 2500 |
| 160N x 110E | 2500 | 2500 |
| 170N x 110E | 2600 | 2500 |
| 180N x 110E | 2350 | 2300 |
| 180N x 100E | 2400 | 2300 |
| 170N x 100E | 2500 | 2350 |
| 160N x 100E | 2450 | 2300 |
| 150N x 100E | 2400 | 2300 |
| 140N x 100E | 2450 | 2400 |

* Background = 2500 cpm

Figure 1
Surface Soil Sample Locations Within Excavated Area



ME-024176

Table 3: Excavated Area Soil Sample Results

| Floor Sample Location Reference # (Figure 1) | Floor Sample Location | Date | Uranium (pCi/g) Gross Alpha Screen |
|--|-----------------------|--------|------------------------------------|
| 1 | 170N x 95E | Dec-92 | 21 |
| 2 | 165N x 95E | Dec-92 | 31 |
| 3 | 155N x 95E | Dec-92 | 37 |
| 4 | 170N x 100E | Dec-92 | 16 |
| 5 | 165N x 100E | Dec-92 | 24 |
| 6 | 160N x 100E | Dec-92 | 28 |
| 7 | 155N x 100E | Dec-92 | 24 |
| 8 | 165N x 105E | Dec-92 | 24 |
| 9 | 160N x 105E | Dec-92 | 24 |
| 10 | 155N x 105E | Dec-92 | 24 |
| 11 | 145N x 105E | Nov-92 | 9 |
| 12 | 170N x 110E | Nov-92 | 53 |
| 13 | 165N x 110E | Nov-92 | 34 |
| 14 | 160N x 110E | Nov-92 | 22 |
| 15 | 150N x 110E | Nov-92 | 26 |
| 16 | 142.5N x 110E | Nov-92 | 24 |
| 17 | 140N x 110E | Nov-92 | 42 |
| 18 | 175N x 115E | Nov-92 | 14 |
| 19 | 170N x 115E | Nov-92 | 22 |
| 20 | 165N x 115E | Nov-92 | 18 |
| 21 | 145N x 115E | Nov-92 | 18 |
| 22 | 170N x 120E | Nov-92 | 34 |
| 23 | 160N x 120E | Nov-92 | 17 |
| 24 | 150N x 120E | Nov-92 | 27 |
| 25 | 145N x 117.5E | Nov-92 | 17 |
| 26 | 140N x 117.5E | Nov-92 | 9 |
| 27 | 185N x 125E | Feb-93 | 25 |
| 28 | 180N x 125E | Nov-92 | 15 |
| 29 | 175N x 125E | Nov-92 | 12 |
| 30 | 165N x 125E | Nov-92 | 11 |
| 31 | 155N x 125E | Nov-92 | 12 |
| 32 | 190N x 130E | Nov-92 | 17 |
| 33 | 185N x 130E | Feb-93 | 35 |
| 34 | 180N x 130E | Feb-93 | 23 |
| 35 | 170N x 130E | Nov-92 | 15 |
| 36 | 160N x 130E | Nov-92 | 27 |
| 37 | 150N x 130E | Nov-92 | 21 |
| 38 | 170N x 132.5E | Feb-93 | 32 |
| 39 | 167.5N x 132.5E | Feb-93 | 23 |
| 40 | 165N x 132.5E | Feb-93 | 33 |
| 41 | 162.5N x 132.5E | Feb-93 | 26 |
| 42 | 185N x 135E | Nov-92 | 50 |
| 43 | 180N x 135E | Feb-93 | 28 |
| 44 | 175N x 135E | Nov-92 | 14 |
| 45 | 165N x 135E | Nov-92 | 26 |
| 46 | 160N x 135E | Feb-93 | 24 |

Table 3: Excavated Area Soil Sample Results

| Floor Sample Location Reference # (Figure 1) | Floor Sample Location | Date | Uranium (pCi/g) Gross Alpha Screen |
|---|--------------------------|--------|---------------------------------------|
| 47 | 155N x 135E | Feb-93 | 22 |
| 48 | 190N x 140E | Nov-92 | 12 |
| 49 | 170N x 140E | Nov-92 | 16 |
| 50 | 160N x 140E | Nov-92 | 24 |
| 51 | 150N x 140E | Nov-92 | 55 |
| 52 | 185N x 145E | Nov-92 | 8 |
| 53 | 180N x 147.5E | Nov-92 | 4 |
| 54 | 200N x 150E | Nov-92 | 29 |
| 55 | 190N x 150E | Nov-92 | 28 |
| 56 | 185N x 150E | Nov-92 | 50 |
| 57 | 180N x 150E | Nov-92 | 48 |
| 58 | 200N x 155E | Nov-92 | 7 |
| 59 | 195N x 155E | Nov-92 | 11 |
| 60 | 185N x 155E | Nov-92 | 21 |
| 61 | 180N x 155E | Nov-92 | 11 |
| 62 | 200N x 160E | Nov-92 | 16 |
| 63 | 200N x 165E | Nov-92 | 19 |
| 64 | 195N x 165E | Nov-92 | 10 |
| 65 | 170N x 180E | Nov-92 | 22 |
| 66 | 160N x 180E | Nov-92 | 33 |
| 67 | 165N x 185E | Nov-92 | 30 |
| 68 | 170N x 190E | Nov-92 | 46 |
| 69 | 160N x 190E | Nov-92 | 23 |
| 70 | 150N x 97.5E | Nov-92 | 19 |
| 71 | 145N x 100E | Nov-92 | 10 |

TABLE 4: GRID CELL AVERAGES OF GROSS ALPHA SCREENING DATA

| GRID CELL LOCATION | GROSS ALPHA DATA (pCi/g) | GRID AVERAGE (pCi/g) |
|---------------------------|--------------------------------------|---------------------------------|
| 190 - 200N x 150 - 160E | 29, 28, 7, 11, 16 | 18.2 |
| 180 -190N x 150 - 160E | 50, 48, 21, 11, 28 | 31.6 |
| 180 - 190N x 140 - 150E | 50, 48, 28, 12, 8, 4 | 25 |
| 180 - 190N x 130 - 140E | 12, 17, 50, 28, 12, 8, 4 | 27.5 |
| 180 - 190N x 120 - 130E | 15, 23, 35, 25, 17 | 23 |
| 170 - 180N x 130 - 140E | 16, 14, 28, 23, 15, 32 | 21.3 |
| 170 --180N x 120 - 130E | 12, 15, 23, 34, 15 | 19.8 |
| 170 - 180N x 110 - 120E | 53, 22, 34, 14 | 30.8 |
| 160 - 170N x 130 - 140E | 6, 24, 22, 24, 32, 23, 26, 33, 15, 2 | 24.2 |
| 160 - 170N x 120 - 130E | 15, 27, 11, 34, 17 | 20.8 |
| 160 - 170N x 110 - 120E | 34, 17, 22, 18, 53, 34, 22 | 28.6 |
| 160 - 170N x 100 - 110E | 53, 34, 22, 24, 24, 24, 16, 28 | 28.1 |
| 160 - 170N x 90 - 100E | 16, 24, 28, 21, 31 | 24 |
| 150 - 150N x 130 - 140E | 24, 55, 24, 22, 27, 21 | 28.8 |
| 150 - 160N x 120 - 130E | 27, 21, 12, 17, 27 | 20.8 |
| 150 - 160N x 110 - 120E | 17, 27, 22, 26 | 23 |
| 150 - 160N x 100 - 110E | 22, 26, 28, 24, 24, 24 | 24.7 |
| 150 - 160N x 90 - 100E | 28, 24, 37, 19 | 27 |
| 140 - 150N x 110 - 120E | 27, 17, 9, 18, 24, 42 | 22.8 |
| 140 - 150N x 100 - 110E | 26, 24, 42, 9, 10 | 22.2 |

Figure 2
Split Spoon Sampling Locations




TABLE 5: PERIMETER SPLIT SPOON SAMPLE RESULTS

| LOCATION | DATE | 0-2' pCi/g | 2'-4' pCi/g | 4'-6' pCi/g | 0-6' AVERAGE pCi/g |
|--------------|--------|---------------|----------------|----------------|-----------------------|
| 200N X 125E | Dec-92 | 12 | 10 | 11 | 11 |
| 206N X 130E | Dec-92 | 14 | 24 | 10 | 16 |
| 200N X 135E | Dec-92 | 15 | 9 | 14 | 12.7 |
| 200N X 140E | Dec-92 | 29 | 14 | 8 | 17 |
| 200N X 145E | Dec-92 | 12 | 15 | 5 | 10.7 |
| 205N X 145E | Dec-92 | 21 | 16 | 9 | 15.3 |
| 210N X 165E | Dec-92 | 11 | 21 | 13 | 15 |
| 205N X 153E | Dec-92 | 8 | 12 | 23 | 14.3 |
| 195N X 135E | Dec-92 | 25 | 11 | REF | 18 |
| 175N X 185E | Dec-92 | 18 | 21 | 10 | 16.3 |
| 190N X 174E | Dec-92 | 32 | 5 | 8 | 15 |
| 175N X 163E | Dec-92 | 9 | 5 | 8 | 7.3 |
| 175N X 165E | Dec-92 | 17 | 4 | 6 | 9 |
| 180N X 175E | Dec-92 | 13 | 10 | 5 | 9.3 |
| 175N X 168E | Dec-92 | 13 | 15 | 37 | 21.7 |
| 145N X 135E | Dec-92 | 33 | 23 | 18 | 24.7 |
| 155N X 145E | Dec-92 | 9 | 18 | 13 | 10 |
| 175N X 175E | Dec-92 | 7 | 5 | 9 | 7 |
| 185N X 162E | Dec-92 | .7 | 5 | 11 | 7.7 |
| 140N X 125E | Dec-92 | 29 | 20 | 18 | 22.3 |
| 140N X 103E | Dec-92 | 17 | 13 | 16 | 15.3 |
| 178N X 98E | Dec-92 | 19 | 7 | REF | 13 |
| 135N X 115E | Dec-92 | 17 | 18 | 15 | 16.7 |
| 130N X 110E | Dec-92 | 13 | 18 | 10 | 13.7 |
| 165N X 85E | Dec-92 | 15 | 18 | 25 | 19.3 |
| 150N X 90E | Dec-92 | 8 | 8 | REF | 8 |
| 210N X 150E | Dec-92 | 34 | 25 | 24 | 27.7 |
| 172.5N X 85E | Dec-92 | 12 | 13 | 15 | 13.3 |
| 175N X 90E | Dec-92 | 16 | 13 | REF | 14.5 |

TABLE 5: PERIMETER SPLIT SPOON SAMPLE RESULTS

| LOCATION | DATE | (pCi/g) | | | | | 0-6' AVERAGE |
|-------------|--------|---------|------|------|------|------|--------------|
| | | 0-1' | 1-2' | 2-3' | 3-4' | 4-5' | |
| 145N X 95E | Nov-92 | 10 | 31 | 17 | | 22 | 20 |
| 145N X 140E | Nov-92 | 27 | 34 | 10 | 10 | 9 | 18 |
| 190N X 120E | Nov-92 | 18 | 21 | 15 | | 15 | 17.3 |
| 202N X 170E | Nov-92 | 11 | 16 | | | 12 | 13 |
| 170N X 150E | Nov-92 | 9 | 12 | 6 | 5 | 7 | 7.8 |

| LOCATION | DATE | .5 meter pCi/g | 1 meter pCi/g | 1.5 meter pCi/g | 2 meter pCi/g | 0-2 meter AVG. pCi/g |
|---------------|--------|-------------------|------------------|--------------------|------------------|-------------------------|
| 145N X 145E | Jul-92 | 12 | 10 | | | 11 |
| 175N X 105E | Jul-92 | 9 | 9 | | | 9 |
| 190N X 115E | Jul-92 | 15 | 11 | | | 13 |
| 210N X 130E | Jul-92 | 11 | 5 | | | 8 |
| 202N X 160E | Jul-92 | 16 | 11 | | | 13.5 |
| 200N X 170E | Jul-92 | 9 | 6 | | | 7.5 |
| 172.5N X 160E | Jul-92 | 8 | 8 | | | 8 |
| 177.5N X 140E | Jul-92 | 20 | 9 | 6 | 13 | 12 |
| 147.5N X 125E | Jul-92 | 10 | 6 | | | 8 |

Attachment 1

Post Excavation Radiological Survey Report

POST EXCAVATION RADIOLOGICAL SURVEY REPORT

**TEXAS INSTRUMENTS INCORPORATED
BURIAL SITE
Attleboro, Massachusetts**

Prepared by

Creative Pollution Solutions, Inc.

11/28/92

ME-024184

INTRODUCTION

The post excavation survey for the Texas Instruments Incorporated Building 12 Burial Site was designed in accordance with the Remediation Plan (approved 8/29/92). The remediation of the site included at least all areas outlined in the initial plan. When necessary, additional areas were excavated. The average depth of the excavated area is approximately 1.5 meters. In many areas groundwater was reached. Excavated material was either processed to remove aggregate and/or staged for disposition. A volume of approximately 90,000 ft³ of material was excavated of which approximately 58,000 ft³ was sent to EnviroCare of Utah via rail for final disposition. Figure 1 in Appendix A in this report shows the area of excavation. The excavated area will not be backfilled (except around an exposed fire hydrant) until after ORISE completes necessary sampling to confirm the post excavation survey.

The post excavation survey consists of two parts: a walkover surface scan of the affected area and surface soil sampling of the excavated area.

SURFACE SOIL SAMPLING WITHIN THE EXCAVATED AREA

The soil sampling plan for the excavated area consisted of surface soil samples at each corner and in the middle of each 10 meter x 10 meter grid cell. Wherever possible surface (0-15cm) soil samples of approximately 1 kg each were collected at these points. In some cases excavation equipment had to be used to extract a sample from beneath the standing water. A map of sample locations along with sample results are shown in Appendix A. All of the samples from the excavated area were analyzed using gross alpha screening. The average of all gross alpha screening samples within the excavated area is less than 30 pCi/g (Note: 30 counts/10 min approximately equals 30 pCi/g as correlated with Babcock and Wilcox gamma spectroscopy data -- see Appendix C). The gross alpha screening methodology is described in Appendix B.

SURVEY OF AFFECTED AREA

A walkover surface scan using portable NaI(Tl) gamma scintillation detectors was conducted at 1 meter intervals over the entire affected area. The affected areas consist of any areas in the defined exclusion area (see Health and Safety Plan, 8/92). The grid system established in the ORAU Radiological Survey (1985) was used. A walkover of the excavated area was not possible because of the elevated water table and accumulation of surface water run-off in this area. The walkover survey data is provided in Appendix D.

These surveys were conducted with a Ludlum model 44-2 1" by 1" NaI(Tl) probe coupled to a Ludlum model 2221 Portable Scaler/ratemeter. The purpose of these surveys was to determine and locate any radiological anomalies. The NaI type detectors are inherently highly energy

dependent, but are useful due to its general greater sensitivity. The use of such instruments are well suited for the identification of anomalies, however, care must be given when interpreting the response in terms of exposure rates ($\mu\text{R/h}$). In this regard, a linear response check was performed using a ^{60}Co Source, the results of which are included within Appendix D. The energy distribution of photons encountered in field are characterized by a much lower photon energy distribution which is further confounded by a large degradation of this spectral distribution due to the source incorporation in a soil matrix. The interpretation of exposure rate from this instrument, short of an exhaustive study, is to assume from previous studies (ORAU) that a nominal background exposure rate of $11 \mu\text{R/h}$ exists and that a the NaI(Tl) background response correlates to this value. Even under this presumption certain errors will exist such as variation of background with time. Notwithstanding a response factor from 0.0039 to 0.0034 with an average of 0.0037 is established.

APPENDIX A


EXCAVATION FLOOR SAMPLING ALPHA SCREENING RESULTS

| <u>North</u> | <u>East</u> | <u>Alpha Screen (pCi/g)</u> |
|--------------|-------------|-----------------------------|
| 200 | 150 | 29 |
| 200 | 155 | 7 |
| 200 | 160 | 16 |
| 200 | 165 | 19 |
| 195 | 155 | 11 |
| 195 | 165 | 10 |
| 190 | 130 | 17 |
| 190 | 140 | 12 |
| 190 | 150 | 28 |
| 185 | 125 | 45 |
| 185 | 135 | 50 |
| 185 | 145 | 8 |
| 185 | 152 | 50 |
| 185 | 155 | 21 |
| 180 | 125 | 15 |
| 180 | 130 | 14 |
| 180 | 150 | 4 |
| 180 | 152 | 48 |
| 180 | 155 | 11 |
| 175 | 115 | 14 |
| 175 | 125 | 12 |
| 175 | 135 | 14 |
| 170 | 110 | 53 |
| 170 | 115 | 22 |
| 170 | 120 | 34 |
| 170 | 130 | 7 |
| 170 | 140 | 16 |
| 170 | 180 | 22 |
| 170 | 190 | 46 |

| <u>North</u> | <u>East</u> | <u>Alpha Screen (pCi/g)</u> |
|--------------|-------------|-----------------------------|
| 165 | 110 | 34 |
| 165 | 115 | 18 |
| 165 | 125 | 11 |
| 165 | 135 | 22 |
| 165 | 185 | 30 |
| 160 | 110 | 22 |
| 160 | 120 | 17 |
| 160 | 130 | 27 |
| 160 | 140 | 24 |
| 160 | 180 | 33 |
| 160 | 190 | 23 |
| 155 | 125 | 12 |
| 155 | 135 | 25 |
| 150 | 110 | 26 |
| 150 | 120 | 27 |
| 150 | 130 | 21 |
| 150 | 140 | 55 |
| 145 | 105 | 9 |
| 145 | 115 | 18 |
| 145 | 120 | 17 |
| 142 | 110 | 24 |
| 140 | 110 | 42 |
| 140 | 120 | 9 |

Average of values = 23.10 pCi/g
Standard deviation = 13.23

Figure 1
Surface Soil Sample Locations Within Excavated Area



ME-024189

APPENDIX B

ALPHA SCREENING METHODOLOGY

The alpha screening technique employed was gross alpha counting of a soil sample in intimate contact with a ZnS(Ag) detector. Using this method the ZnS(Ag) disc is disposable.

The method employed in the field was as follows:

- 1) Approximately 1 kg soil sample obtained
- 2) Sample homogenized by mixing (in larger container if necessary)
- 3) An aliquot of the homogenized sample is then (approximately 20-40 grams) dried in an oven at about 100° C for approximately 10 minutes. The sample is then allowed to cool.
- 4) The sample is then sieved and placed in direct contact with the phosphor side of the ZnS dish assembly.
- 5) The sample is then placed in direct contact with a photomultiplier tube and counted for 10 minutes.

The counts obtained have been correlated to both alpha spectroscopy and gamma spectroscopy. The correlation to gamma spectroscopy is attached in Appendix C and the correlation to alpha spectroscopy has been demonstrated in previous reports.

APPENDIX C

COMPARISON OF ALPHA SCREENING AND GAMMA SPECTROSCOPY


Since the post excavation survey results were obtained using alpha screening 10 split samples were sent to both ORISE and an outside laboratory to establish a correlation between the gamma spectroscopy data and the alpha screening data. The comparison with one set of gamma spectroscopy results are shown below.

Notes regarding attached graph:

- 1) alpha screening result is based on an average of 5-10 samples
- 2) gamma spec data assumed an activity ratio (U-234/U-235) of 22.

Comparison of Alpha Screening and Gamma Spectroscopy for Uranium in Soil

| SAMPLE ID | ALPHA SCREEN (TOTAL U pCi/g) | GAMMA SPEC (TOTAL U pCi/g) |
|-----------|---------------------------------|-------------------------------|
| 138N-113E | 21.4 | 1.25 |
| 134N-118E | 12.8 | 4.65 |
| MP5 | 15.9 | 7.1 |
| MP1-2 | 19.2 | 11.65 |
| 235N-156E | 19 | 12.49 |
| MP4 | 14.2 | 21.82 |
| Rock Pile | 25.8 | 26.96 |
| BFP | 29.9 | 36.76 |
| RS410/411 | 75.3 | 56.99 |
| RS414 | 85 | 90.77 |



APPENDIX D

WALKOVER SURVEY RESULTS


NOTE:

The attached represents the results of the walk over survey. The results presented are in the units of counts per minute (cpm)

Determination of the Response of the NaI(Tl) Detector for Radiological Field Surveys

| | Bkg | 2.5 meter | 2.0 meter | 1.5 meter | 1.0 meter |
|----------|---------|-----------|-----------|-----------|-----------|
| 1.00 | 5206.00 | 7455.00 | 8444.00 | 10938.00 | 17472.00 |
| 2.00 | 5283.00 | 7277.00 | 8564.00 | 10835.00 | 17646.00 |
| 3.00 | 5143.00 | 7441.00 | 8751.00 | 11107.00 | 17738.00 |
| 4.00 | 4959.00 | 7489.00 | 8552.00 | 10797.00 | 17744.00 |
| 5.00 | 5056.00 | 7589.00 | 8418.00 | 10864.00 | 17790.00 |
| 6.00 | 5105.00 | 7602.00 | 8334.00 | 10542.00 | 18064.00 |
| Average | 5125.33 | 7475.50 | 8510.50 | 10847.17 | 17742.33 |
| Exp. Err | 113.64 | 118.39 | 145.98 | 185.39 | 193.97 |
| Th. Err. | 71.59 | 86.46 | 92.25 | 104.15 | 133.20 |
| Chi. Sq. | 2.52 | 1.87 | 2.50 | 3.17 | 2.12 |

| | | | | |
|------------------------------|-----------|-----------|-----------|-----------|
| Net Response, cpm | 2350.17 | 3385.17 | 5721.83 | 12617.00 |
| Dose Rate, uR/h | 14.58 | 28.13 | 50 | 112.5 |
| Calibration Factor, uR/h/cpm | 0.0062038 | 0.0083083 | 0.0087385 | 0.0089165 |



Determination of the Response of the NaI(Tl) Detector for Radiological Field Surveys

Regression Statistics

| | |
|-------------------|-----------|
| Multiple R | 0.9962444 |
| R Square | 0.9925029 |
| Adjusted R Square | -1.333333 |
| Standard Error | 3.7517943 |
| Observations | 1 |

Analysis of Variance

| | <i>df</i> | <i>Sum of Squares</i> | <i>Mean Square</i> | <i>F</i> |
|------------|-----------|-----------------------|--------------------|----------|
| Regression | 4 | 5590.341138 | 1397.58528 | 397.16 |
| Residual | 3 | 42.22788077 | 14.0759603 | |
| Total | 7 | 5632.569019 | | |

| | <i>Coefficients</i> | <i>Standard Error</i> | <i>t Statistic</i> | <i>P-value</i> | <i>Lower 95%</i> | <i>Upper 95%</i> |
|-----------|---------------------|-----------------------|--------------------|----------------|------------------|------------------|
| Intercept | 0 | | | | | |
| Slope | 0.0087835 | 0.000259572 | 33.8385201 | 5E-09 | 0.0079575 | 0.00961 |

Walk Over Surface Scan

| Coordinates | 105 | 106 | 107 | 108 | 109 | 110 | 111 | 112 | 113 |
|-------------|------|------|------|------|------|------|------|------|------|
| East | | | | | | | | | |
| North | | | | | | | | | |
| 120 | | | | | | | | | |
| 121 | | | | | | | | | |
| 122 | | | | | | | | | |
| 123 | | | | | | | | | |
| 124 | | | | | | | | | |
| 125 | | | | | | | | | |
| 126 | | | | | | | | | |
| 127 | | | | | | | | | |
| 128 | | | | | | | 3200 | 3200 | 2500 |
| 129 | | | | | | 2600 | 2800 | 2800 | 2500 |
| 130 | | | | | | 2700 | 2600 | 2700 | 3500 |
| 131 | | | | | | 3000 | 2800 | 2800 | 2900 |
| 132 | | | | 2800 | 2500 | 2500 | 2500 | 2500 | 2500 |
| 133 | | | | 2500 | 2600 | 3100 | 3100 | 3200 | 2900 |
| 134 | tar | tar | tar | 3000 | 3000 | 2800 | 3000 | 2800 | 2800 |
| 135 | tar | 3200 | 2500 | 3200 | 3100 | 3000 | 3100 | 3200 | 3000 |
| 136 | tar | 2900 | 3000 | 3300 | 3000 | 3000 | 3300 | 3100 | 3100 |
| 137 | tar | 3000 | 2900 | 3000 | 3100 | 3000 | 2900 | 3300 | 3200 |
| 138 | 2900 | 2900 | 3100 | 3100 | 3200 | 3100 | 3000 | 3000 | 3100 |
| 139 | 3500 | 3200 | 3000 | 3300 | 3000 | 3200 | 3000 | 3200 | 3200 |
| 140 | 3300 | 2800 | 3600 | 3900 | 3300 | 3300 | 3200 | 3300 | 3300 |
| 141 | 3300 | 3500 | 3500 | 3500 | 3700 | 3300 | 3800 | 3700 | 3700 |
| 142 | tar | 3300 | 3500 | 4000 | 3300 | 3000 | 3200 | 3100 | 3200 |
| 143 | tar | | | | | | | | |
| 144 | tar | | | | | | | | |
| 145 | tar | | | | | | | | |
| 146 | tar | | | | | | | | |
| 147 | tar | | | | | | | | |
| 148 | tar | | | | | | | | |
| 149 | tar | | | | | | | | |
| 150 | tar | | | | | | | | |
| 151 | tar | | | | | | | | |
| 152 | tar | | | | | | | | |
| 153 | tar | | | | | | | | |
| 154 | tar | | | | | | | | |
| 155 | tar | | | | | | | | |
| 156 | tar | | | | | | | | |
| 157 | tar | | | | | | | | |
| 158 | tar | | | | | | | | |
| 159 | 3200 | 3500 | 4000 | 3200 | 5500 | 5000 | | | |
| 160 | | 3600 | 3900 | 4000 | 3900 | 3500 | | | |
| 161 | | 3700 | 3800 | 4000 | 4000 | | | | |
| 162 | | 4100 | 4500 | 4000 | 3900 | | | | |
| 163 | | 3500 | 4000 | 3700 | 4000 | | | | |
| 164 | | 3900 | 3900 | 3900 | 3800 | | | | |
| 165 | | 3500 | 4000 | 3900 | 4100 | | | | |
| 166 | | 4000 | 3900 | 3500 | 3800 | | | | |
| 167 | | 3500 | 4200 | 3800 | 4000 | 3800 | | | |
| 168 | | 3700 | 3800 | 3700 | 3800 | 3200 | | | |

Walk Over Surface Scan

| Coordinates | 105 | 106 | 107 | 108 | 109 | 110 | 111 | 112 | 113 |
|-------------|-----|-----|-----|------|------|------|------|------|------|
| East | | | | | | | | | |
| North | | | | | | | | | |
| 169 | | | | 4100 | 4200 | 4100 | | | |
| 170 | | | | 3900 | 3900 | 3900 | | | |
| 171 | | | | 3400 | 3500 | 3700 | | | |
| 172 | | | | 3600 | 3900 | 3700 | | | |
| 173 | | | | 3400 | 3500 | 3600 | | | |
| 174 | | | | 3300 | 3400 | 3500 | | | |
| 175 | | | | 3200 | 3300 | 3400 | | | |
| 176 | | | | 3100 | 3200 | 3200 | | | |
| 177 | | | | 3300 | 3500 | 3500 | 3200 | | |
| 178 | | | | 3500 | 3500 | 3300 | 3500 | 3500 | |
| 179 | | | | 3400 | 3200 | 3100 | 3300 | 3300 | 3200 |
| 180 | | | | | | 3000 | 3600 | 3500 | 3400 |
| 181 | | | | | | 3200 | 3200 | 3100 | 3700 |
| 182 | | | | | | | 3300 | 3400 | 3400 |
| 183 | | | | | | | | | 4000 |
| 184 | | | | | | | | | |
| 185 | | | | | | | | | |
| 186 | | | | | | | | | |
| 187 | | | | | | | | | |
| 188 | | | | | | | | | |
| 189 | | | | | | | | | |
| 190 | | | | | | | | | |
| 191 | | | | | | | | | |
| 192 | | | | | | | | | |
| 193 | | | | | | | | | |
| 194 | | | | | | | | | |
| 195 | | | | | | | | | |
| 196 | | | | | | | | | |
| 197 | | | | | | | | | |
| 198 | | | | | | | | | |
| 199 | | | | | | | | | |
| 200 | | | | | | | | | |
| 201 | | | | | | | | | |
| 202 | | | | | | | | | |
| 203 | | | | | | | | | |
| 204 | | | | | | | | | |
| 205 | | | | | | | | | |
| 206 | | | | | | | | | |
| 207 | | | | | | | | | |
| 208 | | | | | | | | | |
| 209 | | | | | | | | | |
| 210 | | | | | | | | | |
| 211 | | | | | | | | | |
| 212 | | | | | | | | | |
| 213 | | | | | | | | | |
| 214 | | | | | | | | | |
| 215 | | | | | | | | | |
| 216 | | | | | | | | | |
| 217 | | | | | | | | | |

Walk Over Surface Scan

218
219
220



Walk Over Surface Scan

| Coordinates | 114 | 115 | 116 | 117 | 118 | 119 | 120 | 121 | 122 |
|-------------|------|------|------|------|------|------|------|------|------|
| East | | | | | | | | | |
| North | | | | | | | | | |
| 120 | | | | | | | | | |
| 121 | | | | | | | | | |
| 122 | | | | | | | | | |
| 123 | | | | | | | | | |
| 124 | | | | | | | | | |
| 125 | | | | | | | | | |
| 126 | | | | | | | | | |
| 127 | | | | | | | | | |
| 128 | 2500 | 2400 | 2500 | 2500 | | | | | |
| 129 | 2500 | 2900 | 2500 | 2800 | | | | | |
| 130 | 2600 | 2600 | 2500 | 2500 | 2500 | 2500 | 2400 | | |
| 131 | 2500 | 2800 | 2500 | 2500 | 2400 | 2300 | 3000 | | |
| 132 | 2500 | 2800 | 2800 | 2600 | 2500 | 2500 | 2500 | | |
| 133 | 2900 | 3000 | 3100 | 2900 | 2500 | 2500 | 2500 | | |
| 134 | 2700 | 2500 | 2700 | 2500 | 2500 | 2500 | 2500 | | |
| 135 | 2800 | 3000 | 3000 | 3000 | 2900 | 2800 | 2800 | | |
| 136 | 3300 | 3100 | rock | rock | 3200 | 2900 | 2900 | | |
| 137 | 3200 | 3500 | rock | rock | 3100 | 3200 | 3000 | | |
| 138 | 3100 | 3200 | 3100 | 2900 | 3000 | 3000 | 2900 | | |
| 139 | 3100 | 3200 | 3100 | 3200 | 2500 | 3000 | 3000 | | |
| 140 | 3500 | 3400 | 3400 | 3100 | 3000 | 3000 | 3000 | | |
| 141 | 3800 | 3600 | 3300 | 3200 | 3500 | 3200 | 3300 | | |
| 142 | 3400 | 3300 | 3000 | 3200 | 2900 | 2900 | | | |
| 143 | | | | | 2800 | 2800 | | | |
| 144 | | | | | | 2900 | 2900 | 2700 | 2800 |
| 145 | | | | | | 2800 | 3000 | 3100 | 3000 |
| 146 | | | | | | 2900 | 3200 | 3000 | 3200 |
| 147 | | | | | | | 3000 | 3000 | 3100 |
| 148 | | | | | | | | | |
| 149 | | | | | | | | | |
| 150 | | | | | | | | | |
| 151 | | | | | | | | | |
| 152 | | | | | | | | | |
| 153 | | | | | | | | | |
| 154 | | | | | | | | | |
| 155 | | | | | | | | | |
| 156 | | | | | | | | | |
| 157 | | | | | | | | | |
| 158 | | | | | | | | | |
| 159 | | | | | | | | | |
| 160 | | | | | | | | | |
| 161 | | | | | | | | | |
| 162 | | | | | | | | | |
| 163 | | | | | | | | | |
| 164 | | | | | | | | | |
| 165 | | | | | | | | | |
| 166 | | | | | | | | | |
| 167 | | | | | | | | | |
| 168 | | | | | | | | | |

Walk Over Surface Scan

| Coordinates | 114 | 115 | 116 | 117 | 118 | 119 | 120 | 121 | 122 |
|-------------|------|------|------|------|------|------|------|------|------|
| East | | | | | | | | | |
| North | | | | | | | | | |
| 169 | | | | | | | | | |
| 170 | | | | | | | | | |
| 171 | | | | | | | | | |
| 172 | | | | | | | | | |
| 173 | | | | | | | | | |
| 174 | | | | | | | | | |
| 175 | | | | | | | | | |
| 176 | | | | | | | | | |
| 177 | | | | | | | | | |
| 178 | | | | | | | | | |
| 179 | 3200 | 3200 | 3300 | 3500 | 3500 | 3300 | 3400 | | |
| 180 | 3400 | 3400 | 3000 | 3000 | 3000 | 3300 | 3500 | 3400 | |
| 181 | 3300 | 3200 | 3600 | 3200 | 3200 | 3000 | 3500 | 3600 | 3400 |
| 182 | 3300 | 3400 | 3400 | 3100 | 3000 | 3000 | 3200 | 3500 | 3200 |
| 183 | 3300 | 3300 | 3100 | 3200 | 3100 | 3000 | 3100 | 3300 | 3200 |
| 184 | 3100 | 3400 | 3000 | 3100 | 3200 | 3100 | 3100 | 3300 | 3200 |
| 185 | | 3500 | 3200 | 3100 | 3300 | 3000 | 3200 | 3500 | 3200 |
| 186 | | 3400 | 3100 | 3200 | 3300 | 3200 | 2900 | 3500 | 3500 |
| 187 | | 3400 | 3200 | 3100 | 3500 | 3000 | 3000 | 3500 | 3200 |
| 188 | | 3200 | 3100 | 3300 | 3500 | 3200 | 3000 | 3200 | 3400 |
| 189 | | 3300 | 3200 | 3100 | 3000 | 3200 | 3200 | 3200 | 3200 |
| 190 | | 3500 | 3200 | 3100 | 3000 | 3200 | 3000 | 3200 | 3700 |
| 191 | | 3500 | 3200 | 3100 | 3200 | 3100 | 3500 | 3200 | 3700 |
| 192 | | 3400 | 3200 | 3000 | 3500 | 3200 | 3200 | 3500 | 3700 |
| 193 | | 3300 | 3400 | 3200 | 3500 | 3100 | 3200 | 3500 | 3700 |
| 194 | | 3400 | 3400 | 3100 | 3200 | 3200 | 3400 | 3500 | 3400 |
| 195 | | 3400 | 3400 | 3100 | 3000 | 3200 | 3500 | 3300 | 3300 |
| 196 | | 3400 | 3200 | 3000 | 3100 | 3300 | 3500 | 3000 | 3500 |
| 197 | | 3400 | 3400 | 3100 | 3100 | 3600 | 3500 | 3100 | 3500 |
| 198 | | 3200 | 3300 | 3300 | 3400 | 3000 | 3100 | 3100 | 3300 |
| 199 | | 3300 | 3300 | 3200 | 3300 | 3100 | 3100 | 3000 | 3300 |
| 200 | | 3400 | 3100 | 3000 | 3000 | 3100 | 3300 | 3300 | 3400 |
| 201 | | | | | | | 3300 | 3400 | 3300 |
| 202 | | | | | | | 3200 | 3100 | 3400 |
| 203 | | | | | | | 3100 | 3200 | 3200 |
| 204 | | | | | | | 3200 | 3200 | 3100 |
| 205 | | | | | | | 3200 | 3100 | 3400 |
| 206 | | | | | | | 3100 | 3100 | 3200 |
| 207 | | | | | | | 3000 | 3100 | 3500 |
| 208 | | | | | | | 3000 | 3300 | 3500 |
| 209 | | | | | | | 3000 | 3200 | 3600 |
| 210 | | | | | | | 3500 | 3300 | 3200 |
| 211 | | | | | | | 3400 | 3200 | 3200 |
| 212 | | 3300 | 3200 | 4400 | 3600 | 3400 | 3400 | 3500 | 3200 |
| 213 | | 3200 | 3200 | 3700 | 3600 | 3300 | 3400 | 3300 | 3100 |
| 214 | | 3400 | 3100 | 3600 | 3700 | 3500 | 3300 | 3200 | 3100 |
| 215 | | 3300 | 3800 | 3600 | 4600 | 3400 | 3300 | 3300 | 3400 |
| 216 | | 3300 | 3500 | 3800 | 3600 | 3800 | 3400 | 3400 | 3600 |
| 217 | | 3900 | 4100 | 3900 | 3600 | 4000 | 4000 | 3800 | 3600 |

Walk Over Surface Scan

| | | | | | | | | |
|-----|------|------|------|------|------|------|------|------|
| 218 | 4100 | 4300 | 4100 | 4000 | 3800 | 3800 | 4000 | 3600 |
| 219 | 4000 | 3800 | 4200 | 4100 | 3800 | 3900 | 3800 | 3600 |
| 220 | 4000 | 4200 | 4600 | 4100 | 3800 | 3900 | 3600 | 3700 |

Walk Over Surface Scan

| Coordinates | 123 | 124 | 125 | 126 | 127 | 128 | 129 | 130 | 131 |
|-------------|------|------|------|------|------|------|------|------|------|
| East | | | | | | | | | |
| North | | | | | | | | | |
| 120 | | | | | | | | | |
| 121 | | | | | | | | | |
| 122 | | | | | | | | | |
| 123 | | | | | | | | | |
| 124 | | | | | | | | | |
| 125 | | | | | | | | | |
| 126 | | | | | | | | | |
| 127 | | | | | | | | | |
| 128 | | | | | | | | | |
| 129 | | | | | | | | | |
| 130 | | | | | | | | | |
| 131 | | | | | | | | | |
| 132 | | | | | | | | | |
| 133 | | | | | | | | | |
| 134 | | | | | | | | | |
| 135 | | | | | | | | | |
| 136 | | | | | | | | | |
| 137 | | | | | | | | | |
| 138 | | | | | | | | | |
| 139 | | | | | | | | | |
| 140 | | | | | | | | | |
| 141 | | | | | | | | | |
| 142 | | | | | | | | | |
| 143 | | | | | | | | | |
| 144 | 2900 | 3000 | 3000 | 3000 | 3000 | 3000 | 3000 | 2900 | |
| 145 | 3000 | 3200 | 3200 | | | | | | 3000 |
| 146 | 3400 | 3400 | 3500 | | | | | | |
| 147 | 3000 | 3100 | | | | | | | |
| 148 | | | | | | | | | |
| 149 | | | | | | | | | |
| 150 | | | | | | | | | |
| 151 | | | | | | | | | |
| 152 | | | | | | | | | |
| 153 | | | | | | | | | |
| 154 | | | | | | | | | |
| 155 | | | | | | | | | |
| 156 | | | | | | | | | |
| 157 | | | | | | | | | |
| 158 | | | | | | | | | |
| 159 | | | | | | | | | |
| 160 | | | | | | | | | |
| 161 | | | | | | | | | |
| 162 | | | | | | | | | |
| 163 | | | | | | | | | |
| 164 | | | | | | | | | |
| 165 | | | | | | | | | |
| 166 | | | | | | | | | |
| 167 | | | | | | | | | |
| 168 | | | | | | | | | |

Walk Over Surface Scan

| Coordinates | 123 | 124 | 125 | 126 | 127 | 128 | 129 | 130 | 131 |
|-------------|------|------|------|------|------|------|------|------|------|
| North | | | | | | | | | |
| 169 | | | | | | | | | |
| 170 | | | | | | | | | |
| 171 | | | | | | | | | |
| 172 | | | | | | | | | |
| 173 | | | | | | | | | |
| 174 | | | | | | | | | |
| 175 | | | | | | | | | |
| 176 | | | | | | | | | |
| 177 | | | | | | | | | |
| 178 | | | | | | | | | |
| 179 | | | | | | | | | |
| 180 | | | | | | | | | |
| 181 | | | | | | | | | |
| 182 | 3100 | | | | | | | | |
| 183 | 3400 | | | | | | | | |
| 184 | 3500 | 3200 | | | | | | | |
| 185 | 3700 | 3200 | | | | | | | |
| 186 | 3400 | 3600 | | | | | | | |
| 187 | 3500 | 3700 | 3400 | | | | | | |
| 188 | 3500 | 3200 | 3400 | | | | | | |
| 189 | 3400 | 3400 | 3700 | 3200 | | | | | |
| 190 | 3700 | 3400 | 3200 | 3600 | 3600 | | | | |
| 191 | 3600 | 3600 | 3200 | 3700 | 3800 | 3700 | 3600 | 3700 | 4500 |
| 192 | 3500 | 3600 | 3600 | 3700 | 4300 | 3800 | 4000 | 5000 | 6500 |
| 193 | 3500 | 3900 | 3700 | 3600 | 4100 | 3800 | 4000 | 4500 | 3700 |
| 194 | 3300 | 3700 | 3600 | 3600 | 3600 | 3600 | 3500 | 4000 | 3600 |
| 195 | 3200 | 3500 | 3600 | 3300 | 3400 | 3600 | 3500 | 3700 | 3700 |
| 196 | 3500 | 3300 | 3100 | 3300 | 3400 | 3600 | 3400 | 3500 | 3700 |
| 197 | 3500 | 3700 | 3500 | 3300 | 3200 | 3700 | 3100 | 3500 | 3600 |
| 198 | 3500 | 3600 | 3400 | 3500 | 3400 | 3200 | 3100 | 3700 | 3600 |
| 199 | 3200 | 3200 | 3000 | 3300 | 3300 | 3200 | 3100 | 3600 | 3500 |
| 200 | 3300 | 3400 | 3200 | 3500 | 3300 | 3400 | 3400 | 3600 | 3400 |
| 201 | 3200 | 3400 | 3200 | 3400 | 3500 | 3400 | 3400 | 3700 | 3200 |
| 202 | 3300 | 3300 | 3800 | 3100 | 3600 | 3200 | 3200 | 3900 | 3100 |
| 203 | 3500 | 3100 | 3400 | 3200 | 3300 | 3000 | 3400 | 3300 | 3000 |
| 204 | 3300 | 3100 | 3500 | 3300 | 3400 | 3000 | 3500 | 3300 | 3400 |
| 205 | 3200 | 3200 | 3500 | 3400 | 3600 | 3200 | 3500 | 3600 | 3500 |
| 206 | 3100 | 3500 | 3400 | 3400 | 3100 | 3700 | 3400 | 3400 | 3600 |
| 207 | 3400 | 3300 | 3300 | 3400 | 3300 | 3500 | 3500 | 3600 | 3600 |
| 208 | 3400 | 3200 | 3400 | 3200 | 3700 | 3400 | 3400 | 3400 | 3200 |
| 209 | 3200 | 3300 | 3400 | 3300 | 3200 | 3500 | 3300 | 3200 | 3100 |
| 210 | 3300 | 3300 | 3400 | 3500 | 3200 | 3300 | 3200 | 3200 | 3100 |
| 211 | 3200 | 3200 | 3100 | 3200 | 3500 | 3600 | 3200 | 3300 | 3100 |
| 212 | 3200 | 3200 | 3300 | 3300 | 3300 | 3500 | 3100 | 3400 | 3200 |
| 213 | 3300 | 3300 | 3300 | 3200 | 3700 | 3500 | 3500 | 3300 | 3200 |
| 214 | 3300 | 3600 | 3300 | 3500 | 3200 | 3400 | 3500 | 3200 | 3400 |
| 215 | 3300 | 3700 | 3600 | 3700 | 3500 | 3600 | 3600 | 3600 | 3500 |
| 216 | 3800 | 3800 | 3500 | 3600 | 3500 | 3800 | 3600 | 3800 | 3500 |
| 217 | 4200 | 4000 | 3800 | 4000 | 3800 | 4000 | 4100 | 3800 | 3500 |

Walk Over Surface Scan

| | | | | | | | | | |
|-----|------|------|------|------|------|------|------|------|------|
| 218 | 4000 | 3600 | 4000 | 3900 | 3600 | 3800 | 4000 | 3700 | 3500 |
| 219 | 4000 | 3600 | 3800 | 4200 | 3600 | 3800 | 3700 | 4600 | 3600 |
| 220 | 3600 | 3800 | 3600 | 3400 | 3600 | 3400 | 3600 | 3300 | 3100 |

Walk Over Surface Scan

| Coordinates | 132 | 133 | 134 | 135 | 136 | 137 | 138 | 139 | 140 |
|-------------|------|------|------|------|------|------|------|------|------|
| East | | | | | | | | | |
| North | | | | | | | | | |
| 120 | | | | | | | | | |
| 121 | | | | | | | | | |
| 122 | | | | | | | | | |
| 123 | | | | | | | | | |
| 124 | | | | | | | | | |
| 125 | | | | | | | | | |
| 126 | | | | | | | | | |
| 127 | | | | | | | | | |
| 128 | | | | | | | | | |
| 129 | | | | | | | | | |
| 130 | | | | | | | | | |
| 131 | | | | | | | | | |
| 132 | | | | | | | | | |
| 133 | | | | | | | | | |
| 134 | | | | | | | | | |
| 135 | | | | | | | | | |
| 136 | | | | | | | | | |
| 137 | | | | | | | | | |
| 138 | | | | | | | | | |
| 139 | | | | | | | | | |
| 140 | | | | | | | | | |
| 141 | | | | | | | | | |
| 142 | | | | | | | | | |
| 143 | | | | | | | | | |
| 144 | | | | | | | | | |
| 145 | 3000 | 3000 | 2900 | 2900 | 3000 | 3000 | 3000 | 2900 | 3000 |
| 146 | 3000 | 3000 | 3000 | 2900 | 2900 | 3000 | 3000 | 2800 | 3000 |
| 147 | 3000 | 3000 | 2800 | 3000 | 3000 | 3000 | 3000 | 3000 | 3000 |
| 148 | 3000 | 3000 | 3000 | 3000 | 3100 | 3000 | 3200 | 2900 | 3000 |
| 149 | 3200 | | | | | | 3200 | 3000 | 3000 |
| 150 | | | | | | | 3300 | 3200 | 3200 |
| 151 | | | | | | | | | |
| 152 | | | | | | | | | |
| 153 | | | | | | | | | |
| 154 | | | | | | | | | |
| 155 | | | | | | | | | |
| 156 | | | | | | | | | |
| 157 | | | | | | | | | |
| 158 | | | | | | | | | |
| 159 | | | | | | | | | |
| 160 | | | | | | | | | |
| 161 | | | | | | | | | |
| 162 | | | | | | | | | |
| 163 | | | | | | | | | |
| 164 | | | | | | | | | |
| 165 | | | | | | | | | |
| 166 | | | | | | | | | |
| 167 | | | | | | | | | |
| 168 | | | | | | | | | |

Walk Over Surface Scan

| Coordinates | 132 | 133 | 134 | 135 | 136 | 137 | 138 | 139 | 140 |
|-------------|------|-------|------|------|------|------|------|------|------|
| East | | | | | | | | | |
| North | | | | | | | | | |
| 169 | | | | | | | | | |
| 170 | | | | | | | | | 4100 |
| 171 | | | | | | | | | 4200 |
| 172 | | | | | | SW | SW | SW | SW |
| 173 | | | | | | SW | SW | SW | SW |
| 174 | | | | | | SW | SW | SW | SW |
| 175 | | | | | | | | 3500 | 3400 |
| 176 | | | | | | | | 3200 | 3400 |
| 177 | | | | | | | | 3200 | 3500 |
| 178 | | | | | | | | 3400 | 3500 |
| 179 | | | | | | | | 3500 | 3600 |
| 180 | | | | | | | | 3500 | 3700 |
| 181 | | | | | | | | | |
| 182 | | | | | | | | | |
| 183 | | | | | | | | | |
| 184 | | | | | | | | | |
| 185 | | | | | | | | | |
| 186 | | | | | | | | | |
| 187 | | | | | | | | | |
| 188 | | | | | | | | | |
| 189 | | | | | | | | | |
| 190 | | | 3800 | 4300 | 5500 | 3900 | 3700 | 4000 | 3700 |
| 191 | 4500 | 5500 | 3800 | 5500 | 4800 | 3400 | 3700 | 3900 | 4000 |
| 192 | 6100 | 5000 | 4100 | 3500 | 3800 | 3200 | 3700 | 3500 | 4000 |
| 193 | 5700 | 10000 | 3800 | 3400 | 3200 | 3400 | 3400 | 3500 | 3400 |
| 194 | 4400 | 4100 | 3700 | 3300 | 3200 | 3200 | 3200 | 3300 | 3500 |
| 195 | 3300 | 3400 | 3700 | 3200 | 3000 | 3300 | 3200 | 3400 | 3500 |
| 196 | 3200 | 3500 | 3500 | 3300 | 3000 | 3100 | 3100 | 3400 | 3400 |
| 197 | 3200 | 3100 | 3300 | 3500 | 3000 | 3200 | 3200 | 3300 | 3200 |
| 198 | 3500 | 3300 | 3400 | 3600 | 3200 | 3200 | 3300 | 3100 | 3300 |
| 199 | 3600 | 3300 | 3400 | 3500 | 3000 | 3900 | 3200 | 3200 | 3500 |
| 200 | 3500 | 3400 | 3400 | 3800 | 3700 | 3500 | 3200 | 3400 | 3200 |
| 201 | 3400 | 3400 | 3000 | 4000 | 3500 | 3300 | 3400 | 3100 | 3300 |
| 202 | 3600 | 3700 | 3400 | 3800 | 3400 | 3500 | 3400 | 3400 | 3300 |
| 203 | 3500 | 3600 | 3700 | 3900 | 3700 | 3200 | 3400 | 3400 | 3500 |
| 204 | 3500 | 3600 | 3800 | 4400 | 3500 | 3300 | 5800 | 3200 | 3400 |
| 205 | 3500 | 3600 | 4100 | 3600 | 3900 | 3500 | 3400 | 3500 | 3400 |
| 206 | 3700 | 3500 | 3800 | 3500 | 3700 | 3100 | 3100 | 3600 | 3500 |
| 207 | 3800 | 3700 | 3500 | 3400 | 3500 | 3200 | 3100 | 3400 | 3500 |
| 208 | 3400 | 3100 | 3200 | 3300 | 3200 | 3100 | 3300 | 3300 | 3300 |
| 209 | 3100 | 3200 | 3300 | 3500 | 3400 | 3300 | 3500 | 3400 | 3400 |
| 210 | 3300 | 3300 | 3400 | 3500 | 3300 | 3100 | 3300 | 3500 | 3500 |
| 211 | 3100 | 3100 | 3100 | 3200 | 3200 | 3200 | 3200 | 3200 | 3300 |
| 212 | 3100 | 3100 | 3300 | 3400 | 3300 | 3400 | 3600 | 3200 | 3400 |
| 213 | 3600 | 3200 | 3500 | 3600 | 3600 | 3400 | 3600 | 3300 | 3600 |
| 214 | 3500 | 3200 | 4000 | 3500 | 3800 | 3800 | 3800 | 3300 | 3600 |
| 215 | 3600 | 3400 | 4000 | 3600 | 3800 | 4000 | 3800 | 3500 | 3600 |
| 216 | 3700 | 4100 | 3700 | 4000 | 3900 | 4400 | 4100 | 3800 | 3800 |
| 217 | 3800 | 3800 | 3700 | 3900 | 3800 | 4200 | 4300 | 4000 | |

Walk Over Surface Scan

| | | | | | | | | | |
|-----|------|------|------|------|------|------|------|--|--|
| 218 | 3500 | 3600 | 3400 | 3900 | 3200 | 4200 | 4200 | | |
| 219 | 3600 | 3400 | 3200 | 3400 | 3000 | 3600 | | | |
| 220 | 3300 | 3100 | 3300 | 3100 | | | | | |

Walk Over Surface Scan

| Coordinates | 141 | 142 | 143 | 144 | 145 | 146 | 147 | 148 | 149 |
|-------------|------|------|------|------|------|------|------|------|------|
| East | | | | | | | | | |
| North | | | | | | | | | |
| 120 | | | | | | | | | |
| 121 | | | | | | | | | |
| 122 | | | | | | | | | |
| 123 | | | | | | | | | |
| 124 | | | | | | | | | |
| 125 | | | | | | | | | |
| 126 | | | | | | | | | |
| 127 | | | | | | | | | |
| 128 | | | | | | | | | |
| 129 | | | | | | | | | |
| 130 | | | | | | | | | |
| 131 | | | | | | | | | |
| 132 | | | | | | | | | |
| 133 | | | | | | | | | |
| 134 | | | | | | | | | |
| 135 | | | | | | | | | |
| 136 | | | | | | | | | |
| 137 | | | | | | | | | |
| 138 | | | | | | | | | |
| 139 | | | | | | | | | |
| 140 | | | | | | | | | |
| 141 | | | | | | | | | |
| 142 | | | | | | | | | |
| 143 | | | | | | | | | |
| 144 | | | | | | | | | |
| 145 | 2800 | 2900 | 3100 | 3100 | 3100 | 3000 | 3300 | 3200 | 3100 |
| 146 | 2700 | 3000 | 3300 | 3400 | 2900 | 3200 | 3700 | 3000 | 3200 |
| 147 | 2800 | 3000 | 3400 | 3500 | 2800 | 3400 | 3800 | 3300 | 3200 |
| 148 | 2800 | 3200 | 3300 | 3300 | 3100 | 3900 | 3700 | 3400 | 3300 |
| 149 | 2900 | 3000 | 3200 | 3300 | 3100 | 3500 | 3200 | 3500 | 3200 |
| 150 | 3200 | 3400 | 3200 | 3100 | 3000 | 3500 | 3500 | 3200 | 3000 |
| 151 | | | 3200 | 3200 | 3200 | 3000 | 2900 | 3200 | 3100 |
| 152 | | | 3000 | 3400 | 3200 | 3100 | 3000 | 3400 | 3100 |
| 153 | | | 3200 | 3200 | 3200 | 3100 | 3000 | 3200 | 3000 |
| 154 | | | 3500 | 3200 | 3300 | 3200 | 3400 | 3100 | 3900 |
| 155 | | | 3400 | 3200 | 3000 | 3200 | 3400 | 3100 | 3000 |
| 156 | | | 3300 | 3100 | 2700 | 3100 | 3200 | 3000 | 3000 |
| 157 | | | 3200 | 3200 | 2900 | 3100 | 3000 | 3000 | 3100 |
| 158 | | | 3400 | 3000 | 3000 | 3000 | 3000 | 3000 | 3200 |
| 159 | | | 3300 | 3000 | 3000 | 3000 | 3000 | 3100 | 3000 |
| 160 | | | 3200 | 3000 | 3200 | 3200 | 3100 | 3000 | 3900 |
| 161 | | | 3400 | 2900 | 3000 | 3100 | 3000 | 2900 | 3000 |
| 162 | | | 3500 | 3000 | 2900 | 3200 | 3000 | 3000 | 3000 |
| 163 | | | 3400 | 3000 | 3100 | 3200 | 3200 | 2900 | 3000 |
| 164 | | | 3500 | 3100 | 3000 | 3300 | 3400 | 3000 | 3200 |
| 165 | | | 3500 | 3300 | 3000 | 3300 | 3300 | 3200 | 3300 |
| 166 | | | 3200 | 3200 | 3000 | 3400 | 3200 | 3000 | 3300 |
| 167 | | | 3200 | 3300 | 3300 | 3200 | 3100 | 3000 | 3200 |
| 168 | | | 3000 | 3100 | 3200 | 3200 | 3200 | 3200 | 3000 |

Walk Over Surface Scan

| Coordinates | 141 | 142 | 143 | 144 | 145 | 146 | 147 | 148 | 149 |
|-------------|------|------|------|------|------|------|------|------|------|
| East | | | | | | | | | |
| North | | | | | | | | | |
| 169 | | | 3000 | 3000 | 3100 | 3200 | 3300 | 3400 | 3300 |
| 170 | 3400 | 3300 | 3500 | 3200 | 3000 | 3100 | 3200 | 3000 | 2500 |
| 171 | 3800 | 3600 | 3500 | 3500 | 3000 | 3000 | 3200 | 3000 | 2900 |
| 172 | sw | sw | sw | sw | sw | sw | sw | sw | sw |
| 173 | sw | sw | sw | sw | sw | sw | sw | sw | sw |
| 174 | sw | sw | sw | sw | sw | sw | sw | sw | sw |
| 175 | 3400 | 3500 | 3400 | 4000 | 3400 | 3700 | 3500 | 3500 | 3400 |
| 176 | 3400 | 3500 | 3700 | 3500 | 3300 | 3500 | 3500 | 3400 | 3400 |
| 177 | 3500 | 3500 | 3600 | 3500 | 3300 | 3800 | 3500 | 4000 | 3900 |
| 178 | 3200 | 3700 | 3500 | 3800 | 9300 | 4000 | 3500 | 3800 | 3900 |
| 179 | 3700 | 3800 | 3500 | 3800 | 6500 | 4000 | 4200 | 3600 | 3500 |
| 180 | 3800 | 4000 | | | | | | | |
| 181 | | | | | | | | | |
| 182 | | | | | | | | | |
| 183 | | | | | | | | | |
| 184 | | | | | | | | | |
| 185 | | | | | | | | | |
| 186 | | | | | | | | | |
| 187 | | | | | | | | | |
| 188 | | | | | | | | | |
| 189 | | | | | | | | | |
| 190 | 3400 | 3600 | 3600 | 3600 | 3300 | 3200 | 3400 | | |
| 191 | 3600 | 3700 | 3800 | 3400 | 3300 | 3400 | 3600 | | |
| 192 | 3400 | 3600 | 3400 | 3600 | 3500 | 3500 | 3600 | | |
| 193 | 3700 | 3600 | 3200 | 3500 | 3700 | 3700 | 3500 | | |
| 194 | 3600 | 3600 | 3500 | 3600 | 3600 | 3400 | 3900 | | |
| 195 | 3200 | 3700 | 3500 | 3500 | 3800 | 3600 | 4700 | | |
| 196 | 3300 | 3500 | 5700 | 3500 | 3900 | 4200 | 3800 | | |
| 197 | 3400 | 3300 | 3200 | 3600 | 3700 | 4800 | 3600 | | |
| 198 | 3500 | 3300 | 3200 | 3400 | 3300 | 3700 | 3500 | 3600 | 3500 |
| 199 | 3500 | 3500 | 3300 | 3400 | 3400 | 3800 | 3200 | 3400 | 3400 |
| 200 | 3200 | 3200 | 3000 | 3300 | 3500 | 3200 | 3200 | 3400 | 3500 |
| 201 | 3200 | 3300 | 3200 | 3200 | 3500 | 3100 | 3500 | 3500 | 3300 |
| 202 | 3000 | 3400 | 3200 | 3100 | 3400 | 3200 | 3400 | 3300 | 3600 |
| 203 | 3300 | 3000 | 3200 | 3100 | 3300 | 3000 | 3400 | 3400 | 3500 |
| 204 | 3300 | 3300 | 3300 | 3100 | 3300 | 3200 | 3400 | 3600 | 3500 |
| 205 | 3400 | 3400 | 3400 | 3400 | 3400 | 3500 | 3700 | 3400 | 3000 |
| 206 | 3400 | 3500 | 3300 | 3400 | 3500 | 4500 | 3600 | 3500 | 3500 |
| 207 | 3300 | 3400 | 3500 | 3400 | 3500 | 3400 | 3600 | 3600 | 3500 |
| 208 | 3500 | 3400 | 3600 | 3600 | 3300 | 3200 | 3700 | 3600 | 3500 |
| 209 | 3600 | 3600 | 4200 | 3600 | 3500 | 3400 | 3700 | 3500 | 3400 |
| 210 | 3400 | 3600 | 3400 | 3700 | 3500 | 3700 | 3700 | 3500 | 3500 |
| 211 | 3200 | 3500 | 3400 | 3500 | 3500 | 3500 | 3400 | 3200 | 3300 |
| 212 | 3200 | 3300 | 3600 | 3600 | 3400 | 3400 | 3400 | | |
| 213 | 3400 | 3300 | 3500 | 3400 | 3300 | 3600 | | | |
| 214 | 3200 | 3500 | 3600 | | | | | | |
| 215 | 3300 | 3600 | | | | | | | |
| 216 | 3600 | | | | | | | | |
| 217 | | | | | | | | | |

Walk Over Surface Scan

218
219
220



Walk Over Surface Scan

| Coordinates East | 150 | 151 | 152 | 153 | 154 | 155 | 156 | 157 | 158 |
|---------------------|-------|-------|-------|-------|-------|-------|-------|------|------|
| North | | | | | | | | | |
| 120 | | | | | | | | | |
| 121 | | | | | | | | | |
| 122 | | | | | | | | | |
| 123 | | | | | | | | | |
| 124 | | | | | | | | | |
| 125 | | | | | | | | | |
| 126 | | | | | | | | | |
| 127 | | | | | | | | | |
| 128 | | | | | | | | | |
| 129 | | | | | | | | | |
| 130 | | | | | | | | | |
| 131 | | | | | | | | | |
| 132 | | | | | | | | | |
| 133 | | | | | | | | | |
| 134 | | | | | | | | | |
| 135 | | | | | | | | | |
| 136 | | | | | | | | | |
| 137 | | | | | | | | | |
| 138 | | | | | | | | | |
| 139 | | | | | | | | | |
| 140 | | | | | | | | | |
| 141 | | | | | | | | | |
| 142 | | | | | | | | | |
| 143 | | | | | | | | | |
| 144 | | | | | | | | | |
| 145 | drive | drive | drive | drive | drive | drive | drive | bldg | bldg |
| 146 | drive | drive | drive | drive | drive | drive | drive | bldg | bldg |
| 147 | drive | drive | drive | drive | drive | drive | drive | bldg | bldg |
| 148 | drive | drive | drive | drive | drive | drive | drive | bldg | bldg |
| 149 | drive | drive | drive | drive | drive | drive | drive | bldg | bldg |
| 150 | drive | drive | drive | drive | drive | drive | drive | bldg | bldg |
| 151 | drive | drive | drive | drive | drive | drive | drive | bldg | bldg |
| 152 | drive | drive | drive | drive | drive | drive | drive | bldg | bldg |
| 153 | drive | drive | drive | drive | drive | drive | drive | bldg | bldg |
| 154 | drive | drive | drive | drive | drive | drive | drive | bldg | bldg |
| 155 | drive | drive | drive | drive | drive | drive | drive | bldg | bldg |
| 156 | drive | drive | drive | drive | drive | drive | drive | tank | tank |
| 157 | drive | drive | drive | drive | drive | drive | drive | tank | tank |
| 158 | drive | drive | drive | drive | drive | drive | drive | tank | tank |
| 159 | drive | drive | drive | drive | drive | drive | drive | tank | tank |
| 160 | drive | drive | drive | drive | drive | drive | drive | tank | tank |
| 161 | drive | drive | drive | drive | drive | drive | drive | tank | tank |
| 162 | drive | drive | drive | drive | drive | drive | drive | tank | tank |
| 163 | drive | drive | drive | drive | drive | drive | drive | tank | tank |
| 164 | drive | drive | drive | drive | drive | drive | drive | tank | tank |
| 165 | drive | drive | drive | drive | drive | drive | drive | tank | tank |
| 166 | drive | drive | drive | drive | drive | drive | drive | tank | tank |
| 167 | drive | drive | drive | drive | drive | drive | drive | tank | tank |
| 168 | drive | drive | drive | drive | drive | drive | drive | tank | tank |

Walk Over Surface Scan

| Coordinates | 150 | 151 | 152 | 153 | 154 | 155 | 156 | 157 | 158 |
|-------------|-------|-------|-------|-------|----------|----------|-------|------|------|
| East | | | | | | | | | |
| North | | | | | | | | | |
| 169 | drive | drive | drive | drive | drive | drive | drive | tank | tank |
| 170 | 2800 | 2800 | 2900 | 2900 | 3000 | 3300 | 3300 | 3200 | 3200 |
| 171 | 2900 | 3000 | 3100 | 3000 | 3200 | 3200 | 3200 | 3000 | 3000 |
| 172 | sw | sw | sw | sw | sw | sw | sw | sw | sw |
| 173 | sw | sw | sw | sw | sw | sw | sw | sw | sw |
| 174 | sw | sw | sw | sw | sw | sw | sw | sw | sw |
| 175 | 3600 | 3400 | 3300 | 3500 | 3700 | 3800 | 3300 | 3200 | 3300 |
| 176 | 3300 | 3600 | 3400 | 3500 | 3500 | 3500 | | | |
| 177 | 3400 | 3900 | 3400 | 3700 | 3500 | 3500 | | | |
| 178 | 3700 | 3700 | 3500 | 3600 | | | | | |
| 179 | 3600 | | | | | | | | |
| 180 | | | | | | | | | |
| 181 | | | | | | | | | |
| 182 | | | | | | | | | |
| 183 | | | | | | | | | |
| 184 | | | | | | | | | |
| 185 | | | | | | | | | |
| 186 | | | | | | | | | |
| 187 | | | | | | | | | |
| 188 | | | | | | | | | |
| 189 | | | | | | | | | |
| 190 | | | | | | | | | |
| 191 | | | | | | | | | |
| 192 | | | | | | | | | |
| 193 | | | | | | | | | |
| 194 | | | | | | | | | |
| 195 | | | | | | | | | |
| 196 | | | | | | | | | |
| 197 | | | | | | | | | |
| 198 | | | | | | | | | |
| 199 | 3500 | 3700 | | | | | 4500 | 4300 | |
| 200 | 3700 | 3800 | 3600 | 7000 | 3800 | 5500 | 4600 | 4100 | 4200 |
| 201 | 3700 | 4500 | 4000 | 3700 | 4000 | 4100 | 4900 | 4200 | 4400 |
| 202 | 3500 | 3900 | 4100 | 3700 | 4100 | 4100 | 3500 | 4000 | 4200 |
| 203 | 3800 | 4200 | 4000 | 4100 | 3600 | 4200 | 3800 | 3600 | 4200 |
| 204 | 3900 | 3900 | 3900 | 5100 | 3800 | 4000 | 3900 | 3600 | 3600 |
| 205 | 3700 | 3600 | 3700 | 4000 | 4000 | 3900 | 3600 | 3700 | 3900 |
| 206 | 3500 | 3600 | 4200 | 3600 | 4000 | 3800 | 3600 | 3400 | 3600 |
| 207 | 3200 | 3800 | 3600 | 3600 | 3900 | 3400 | 4100 | 3300 | 3900 |
| 208 | 3200 | 3400 | 3600 | 3700 | 4000 | 3500 | 4100 | 3700 | |
| 209 | 3400 | 3600 | 3700 | 3700 | 3900 | rockpile | | | |
| 210 | 3200 | 3300 | 3700 | 3900 | rockpile | | | | |
| 211 | 3200 | 3600 | 4000 | | | | | | |
| 212 | | | | | | | | | |
| 213 | | | | | | | | | |
| 214 | | | | | | | | | |
| 215 | | | | | | | | | |
| 216 | | | | | | | | | |
| 217 | | | | | | | | | |

Walk Over Surface Scan

218
219
220



Walk Over Surface Scan

| Coordinates | 159 | 160 | 161 | 162 | 163 | 164 | 165 | 166 | 167 |
|-------------|------|------|------|------|------|------|------|------|------|
| East | | | | | | | | | |
| North | | | | | | | | | |
| 120 | | | | | | | | | |
| 121 | | | | | | | | | |
| 122 | | | | | | | | | |
| 123 | | | | | | | | | |
| 124 | | | | | | | | | |
| 125 | | | | | | | | | |
| 126 | | | | | | | | | |
| 127 | | | | | | | | | |
| 128 | | | | | | | | | |
| 129 | | | | | | | | | |
| 130 | | | | | | | | | |
| 131 | | | | | | | | | |
| 132 | | | | | | | | | |
| 133 | | | | | | | | | |
| 134 | | | | | | | | | |
| 135 | | | | | | | | | |
| 136 | | | | | | | | | |
| 137 | | | | | | | | | |
| 138 | | | | | | | | | |
| 139 | | | | | | | | | |
| 140 | | | | | | | | | |
| 141 | | | | | | | | | |
| 142 | | | | | | | | | |
| 143 | | | | | | | | | |
| 144 | | | | | | | | | |
| 145 | bidg | bidg | bidg | bidg | bidg | bidg | bidg | bidg | |
| 146 | bidg | bidg | bidg | bidg | bidg | bidg | bidg | bidg | |
| 147 | bidg | bidg | bidg | bidg | bidg | bidg | bidg | bidg | |
| 148 | bidg | bidg | bidg | bidg | bidg | bidg | bidg | bidg | |
| 149 | bidg | bidg | bidg | bidg | bidg | bidg | bidg | bidg | |
| 150 | bidg | bidg | bidg | bidg | bidg | bidg | bidg | bidg | |
| 151 | bidg | bidg | bidg | bidg | bidg | bidg | bidg | bidg | |
| 152 | bidg | bidg | bidg | bidg | bidg | bidg | bidg | bidg | |
| 153 | bidg | bidg | bidg | bidg | bidg | bidg | bidg | bidg | |
| 154 | bidg | bidg | bidg | bidg | bidg | bidg | bidg | bidg | |
| 155 | bidg | bidg | bidg | bidg | bidg | bidg | bidg | bidg | |
| 156 | tank | tank | tank | tank | tank | tank | tank | tank | |
| 157 | tank | tank | tank | tank | tank | tank | tank | tank | |
| 158 | tank | tank | tank | tank | tank | tank | tank | tank | |
| 159 | tank | tank | tank | tank | tank | tank | tank | tank | |
| 160 | tank | tank | tank | tank | tank | tank | tank | tank | tar |
| 161 | tank | tank | tank | tank | tank | tank | tank | tank | 3700 |
| 162 | tank | tank | tank | tank | tank | tank | tank | tank | 3900 |
| 163 | tank | tank | tank | tank | tank | tank | tank | tank | 4400 |
| 164 | tank | tank | tank | tank | tank | tank | tank | tank | 5500 |
| 165 | tank | tank | tank | tank | tank | tank | tank | tank | 8200 |
| 166 | tank | tank | tank | tank | tank | tank | tank | tank | 4700 |
| 167 | tank | tank | tank | tank | tank | tank | tank | tank | 4000 |
| 168 | tank | tank | tank | tank | tank | tank | tank | tank | 4000 |

Walk Over Surface Scan

| Coordinates | 159 | 160 | 161 | 162 | 163 | 164 | 165 | 166 | 167 |
|-------------|------|------|------|------|------|------|------|------|------|
| East | | | | | | | | | |
| North | | | | | | | | | |
| 169 | tank | tank | tank | tank | tank | tank | tank | tank | 4700 |
| 170 | 3500 | 3300 | 3300 | 3400 | 3800 | 3500 | 3500 | 3500 | 3500 |
| 171 | 3500 | 3400 | 3400 | 3200 | 3800 | 3300 | 3400 | 3600 | 3200 |
| 172 | sw | sw | sw | sw | sw | sw | sw | sw | sw |
| 173 | sw | sw | sw | sw | sw | sw | sw | sw | sw |
| 174 | sw | sw | sw | sw | sw | sw | sw | sw | sw |
| 175 | 3500 | 3200 | 3500 | 3400 | 3200 | 3200 | 3200 | 3600 | 3200 |
| 176 | 3600 | 3500 | 3700 | 3200 | 3000 | 2200 | 3300 | 3400 | 3200 |
| 177 | 3300 | 3500 | 3400 | 3400 | 3000 | 3300 | 3300 | 3500 | 3500 |
| 178 | 3500 | 3700 | 3300 | 3500 | 3300 | 3400 | 3400 | 3500 | 3900 |
| 179 | 3200 | 3500 | 3500 | 3800 | 3300 | 3400 | 3400 | 3500 | 4100 |
| 180 | 3200 | 3400 | 3600 | 3400 | 3300 | 3500 | 3500 | 4200 | 3800 |
| 181 | 3200 | 3500 | 3300 | 3400 | 3300 | 3500 | 3500 | 3600 | 3700 |
| 182 | 3400 | 3500 | 3500 | 3300 | 3400 | 3500 | 3500 | 3700 | 3500 |
| 183 | 3500 | 3400 | 3400 | 3800 | 3400 | 3400 | 3500 | 3500 | 3500 |
| 184 | 3500 | 3400 | 3500 | 3500 | 3500 | 3700 | 3500 | 3500 | 3500 |
| 185 | 3400 | 3400 | 3400 | 3500 | 3600 | 3500 | 3400 | 3500 | 3500 |
| 186 | 3300 | 3300 | 3700 | 4000 | 3700 | 3600 | 3500 | 3600 | 3700 |
| 187 | 3200 | 3500 | 3800 | 4000 | 3500 | 3700 | 3400 | 3700 | 3700 |
| 188 | 3200 | 4000 | 3700 | 4000 | 4000 | 3700 | 3300 | 3800 | 4000 |
| 189 | 3400 | 3900 | 4000 | 4100 | 3500 | 3800 | 3500 | 3800 | 3500 |
| 190 | 4000 | 3600 | 3500 | 3600 | 4000 | 3800 | 4100 | 3900 | 4100 |
| 191 | | | | | | | 4200 | 4100 | 4100 |
| 192 | | | | | | | 3800 | 4100 | 4100 |
| 193 | | | | | | | 3800 | 3800 | 4000 |
| 194 | | | | | | | 3400 | 3700 | 4200 |
| 195 | | | | | | | 3800 | 4100 | 4100 |
| 196 | | | | | | | 4300 | 3900 | 4200 |
| 197 | | | | | | | 4600 | 4000 | 4900 |
| 198 | | | | | | | 4100 | 3900 | 4300 |
| 199 | | | | | | | 3800 | 3900 | 4100 |
| 200 | 4600 | 4200 | 4100 | 4000 | 4100 | 3800 | 4100 | 3600 | 4200 |
| 201 | 4500 | 5000 | 3700 | 3200 | 3700 | 3500 | 3500 | 3000 | 3500 |
| 202 | 4300 | 4200 | 3700 | 3200 | 3600 | 3500 | 3500 | 3500 | 3700 |
| 203 | 3800 | 3400 | 3500 | 3300 | 3300 | 3500 | 3300 | 3300 | |
| 204 | 3600 | 3600 | 3600 | 3300 | 3300 | 3400 | 3400 | | |
| 205 | 3600 | 3300 | 3400 | 3300 | 3400 | 3500 | | | |
| 206 | 3500 | 3600 | 3300 | 3500 | 3400 | 3600 | | | |
| 207 | 3500 | 3800 | | | 3500 | 3400 | | | |
| 208 | | | | | | | | | |
| 209 | | | | | | | | | |
| 210 | | | | | | | | | |
| 211 | | | | | | | | | |
| 212 | | | | | | | | | |
| 213 | | | | | | | | | |
| 214 | | | | | | | | | |
| 215 | | | | | | | | | |
| 216 | | | | | | | | | |
| 217 | | | | | | | | | |

Walk Over Surface Scan

218
219
220



Walk Over Surface Scan

| Coordinates | 168 | 169 | 170 | 171 | 172 | 173 | 174 | 175 | 176 |
|-------------|------|------|------|------|------|------|-----|-----|-----|
| East | | | | | | | | | |
| North | | | | | | | | | |
| 120 | | | | | | | | | |
| 121 | | | | | | | | | |
| 122 | | | | | | | | | |
| 123 | | | | | | | | | |
| 124 | | | | | | | | | |
| 125 | | | | | | | | | |
| 126 | | | | | | | | | |
| 127 | | | | | | | | | |
| 128 | | | | | | | | | |
| 129 | | | | | | | | | |
| 130 | | | | | | | | | |
| 131 | | | | | | | | | |
| 132 | | | | | | | | | |
| 133 | | | | | | | | | |
| 134 | | | | | | | | | |
| 135 | | | | | | | | | |
| 136 | | | | | | | | | |
| 137 | | | | | | | | | |
| 138 | | | | | | | | | |
| 139 | | | | | | | | | |
| 140 | | | | | | | | | |
| 141 | | | | | | | | | |
| 142 | | | | | | | | | |
| 143 | | | | | | | | | |
| 144 | | | | | | | | | |
| 145 | | | | | | | | | |
| 146 | | | | | | | | | |
| 147 | | | | | | | | | |
| 148 | | | | | | | | | |
| 149 | | | | | | | | | |
| 150 | | | | | | | | | |
| 151 | | | | | | | | | |
| 152 | | | | | | | | | |
| 153 | | | | | | | | | |
| 154 | | | | | | | | | |
| 155 | | | | | | | | | |
| 156 | | | | | | | | | |
| 157 | | | | | | | | | |
| 158 | | | | | | | | | |
| 159 | | | | | | | | | |
| 160 | tar | tar | tar | tar | tar | tar | sw | sw | sw |
| 161 | 3200 | 3200 | 3000 | 3000 | 3200 | 3000 | sw | sw | sw |
| 162 | 3400 | 3500 | 3200 | 3200 | 3500 | 3100 | sw | sw | sw |
| 163 | 3400 | 3500 | 3700 | 3400 | 3500 | 3200 | sw | sw | sw |
| 164 | 3300 | 3700 | 3200 | 3500 | 3500 | 3000 | sw | sw | sw |
| 165 | 3500 | 3600 | 3200 | 3400 | 3600 | 3500 | sw | sw | sw |
| 166 | 3800 | 3600 | 3500 | 3600 | 4000 | 3800 | sw | sw | sw |
| 167 | 3600 | 3600 | 3400 | 3800 | 3600 | 3800 | sw | sw | sw |
| 168 | 3600 | 3600 | 3200 | 3700 | 3900 | 3300 | sw | sw | sw |

Walk Over Surface Scan

| Coordinates | 168 | 169 | 170 | 171 | 172 | 173 | 174 | 175 | 176 |
|-------------|------|------|------|----------|----------|----------|----------|----------|----------|
| North | | | | | | | | | |
| 169 | 3500 | 3500 | 3200 | 3200 | 3500 | 3200 | sw | sw | sw |
| 170 | 3200 | 3400 | 3400 | 3000 | 3200 | 3200 | sw | sw | sw |
| 171 | 3200 | 3100 | 3500 | 3100 | 3300 | 3000 | sw | sw | sw |
| 172 | sw | sw | sw | sw | sw | sw | sw | sw | sw |
| 173 | sw | sw | sw | sw | sw | sw | sw | sw | sw |
| 174 | sw | sw | sw | sw | sw | sw | sw | sw | sw |
| 175 | 3000 | 3000 | 3000 | 2900 | 3100 | 3000 | 3200 | 3700 | 3000 |
| 176 | 2900 | 3000 | 3000 | 2900 | 3200 | 3000 | 3300 | 3200 | 3000 |
| 177 | 3000 | 3500 | 3000 | 3200 | 3200 | 3200 | 3200 | 3300 | 3400 |
| 178 | 3000 | 3700 | 3000 | 3200 | 3200 | 3800 | 3300 | 3700 | 4000 |
| 179 | 3200 | 3800 | 3200 | 3300 | 3400 | 3900 | 3700 | 3500 | 3400 |
| 180 | 4000 | 4500 | 3900 | 4000 | 3200 | 3400 | 3400 | 3500 | 3800 |
| 181 | 3500 | 4000 | 3700 | 3600 | 3200 | 3600 | 3700 | 4000 | 3900 |
| 182 | 3500 | 4000 | 3700 | 4000 | 3400 | 3600 | 3500 | 3600 | 4000 |
| 183 | 3500 | 4000 | 3500 | 3500 | 3400 | 3800 | 4000 | 4000 | 3800 |
| 184 | 3700 | 3600 | 3400 | 3400 | 3700 | 4200 | 3900 | 4100 | 3700 |
| 185 | 3900 | 3500 | 3500 | 3400 | 3900 | 3900 | 3800 | 4100 | 3900 |
| 186 | 4000 | 3600 | 3400 | 3800 | 5300 | 3800 | 4000 | 3800 | 3700 |
| 187 | 4100 | 3700 | 3300 | 3800 | 4000 | 3800 | 3800 | 3600 | 3500 |
| 188 | 4000 | 3700 | 4000 | 4000 | 4000 | 4000 | 3500 | 3700 | 4400 |
| 189 | 4200 | 3800 | 3900 | 3800 | 3900 | 3800 | 5500 | 3800 | 7500 |
| 190 | 3800 | 4400 | 3900 | 4100 | 3800 | 3900 | 3800 | 4000 | 3700 |
| 191 | 8000 | 4000 | 4000 | 3900 | 3900 | 3900 | 3800 | 3900 | 3900 |
| 192 | 4400 | 3900 | 3800 | 3700 | 3800 | 3800 | 3900 | 4100 | 4100 |
| 193 | 4000 | 3900 | 3900 | 3700 | 3800 | 3900 | 4200 | 4200 | 3800 |
| 194 | 4100 | 4000 | 4000 | 3400 | 3700 | 3800 | 3900 | 4000 | 3900 |
| 195 | 3800 | 3900 | 4000 | 3500 | 3700 | 3400 | 3700 | 3700 | 3800 |
| 196 | 3900 | 4200 | 3900 | 3400 | 3600 | 3900 | 3600 | 3600 | 4100 |
| 197 | 3900 | 4000 | 3600 | 3400 | 3400 | 3400 | 3800 | 3400 | 3800 |
| 198 | 3300 | 3500 | 3300 | 3900 | 3800 | 3600 | 3800 | 3600 | rockpile |
| 199 | 3400 | 3300 | 3100 | rockpile | 3700 | 3600 | rockpile | rockpile | rockpile |
| 200 | 3300 | 3200 | 3300 | rockpile | 4000 | rockpile | rockpile | rockpile | |
| 201 | 3700 | | | rockpile | rockpile | rockpile | | | |
| 202 | 3800 | | | | | | | | |
| 203 | | | | | | | | | |
| 204 | | | | | | | | | |
| 205 | | | | | | | | | |
| 206 | | | | | | | | | |
| 207 | | | | | | | | | |
| 208 | | | | | | | | | |
| 209 | | | | | | | | | |
| 210 | | | | | | | | | |
| 211 | | | | | | | | | |
| 212 | | | | | | | | | |
| 213 | | | | | | | | | |
| 214 | | | | | | | | | |
| 215 | | | | | | | | | |
| 216 | | | | | | | | | |
| 217 | | | | | | | | | |

Walk Over Surface Scan

| Coordinates | 177 | 178 | 179 | 180 | 181 | 182 | 183 | 184 | 185 |
|-------------|------|------|------|------|------|------|------|------|------|
| North | | | | | | | | | |
| 120 | | | | | | | | | |
| 121 | | | | | | | | | |
| 122 | | | | | | | | | |
| 123 | | | | | | | | | |
| 124 | | | | | | | | | |
| 125 | | | | | | | | | |
| 126 | | | | | | | | | |
| 127 | | | | | | | | | |
| 128 | | | | | | | | | |
| 129 | | | | | | | | | |
| 130 | | | | | | | | | |
| 131 | | | | | | | | | |
| 132 | | | | | | | | | |
| 133 | | | | | | | | | |
| 134 | | | | | | | | | |
| 135 | | | | | | | | | |
| 136 | | | | | | | | | |
| 137 | | | | | | | | | |
| 138 | | | | | | | | | |
| 139 | | | | | | | | | |
| 140 | | | | | | | | | |
| 141 | | | | | | | | | |
| 142 | | | | | | | | | |
| 143 | | | | | | | | | |
| 144 | | | | | | | | | |
| 145 | | | | | | | | | |
| 146 | | | | | | | | | |
| 147 | | | | | | | | | |
| 148 | | | | | | | | | |
| 149 | | | | | | | | | |
| 150 | | | | | | | | | |
| 151 | | | | | | | | | |
| 152 | | | | | | | | | |
| 153 | | | | | | | | | |
| 154 | | | | | | | | | |
| 155 | | | | | | | | | |
| 156 | | | | | | | | | |
| 157 | | | | | | | | | |
| 158 | | | | | | | | | |
| 159 | | | | | | | | | |
| 160 | 3000 | 3200 | 3400 | 3300 | 3400 | 3500 | 3300 | 3500 | 3500 |
| 161 | 3300 | 3100 | 3200 | 3200 | 3300 | 3300 | 3400 | 3700 | 3600 |
| 162 | 3000 | 3000 | pit | pit | pit | pit | pit | pit | pit |
| 163 | 3200 | 3000 | pit | pit | pit | pit | pit | pit | pit |
| 164 | 3000 | 3000 | pit | pit | pit | pit | pit | pit | pit |
| 165 | 3200 | 3000 | pit | pit | pit | pit | pit | pit | pit |
| 166 | 3200 | 3200 | pit | pit | pit | pit | pit | pit | pit |
| 167 | 3400 | 3200 | pit | pit | pit | pit | pit | pit | pit |
| 168 | 3000 | 3000 | pit | pit | pit | pit | pit | pit | pit |

Walk Over Surface Scan

| Coordinates | 177 | 178 | 179 | 180 | 181 | 182 | 183 | 184 | 185 |
|-------------|----------|----------|----------|----------|------|------|------|------|------|
| East | | | | | | | | | |
| North | | | | | | | | | |
| 169 | 3000 | 3000 | pit | pit | pit | pit | pit | pit | pit |
| 170 | 3100 | 3500 | pit | pit | pit | pit | pit | pit | pit |
| 171 | 3000 | 3400 | pit | pit | pit | pit | pit | pit | pit |
| 172 | sw | sw | sw | sw | sw | sw | sw | sw | sw |
| 173 | sw | sw | sw | sw | sw | sw | sw | sw | sw |
| 174 | sw | sw | sw | sw | sw | sw | sw | sw | sw |
| 175 | 3000 | 3000 | 3200 | 3000 | 3100 | 3200 | 3000 | 3200 | 3200 |
| 176 | 3000 | 3000 | 3300 | 3100 | 3100 | 3000 | 3000 | 3400 | 3100 |
| 177 | 3000 | 3300 | 3000 | 3200 | 3200 | 3200 | 3100 | 3500 | 3000 |
| 178 | 3100 | 3500 | 3500 | 3200 | 3300 | 3500 | 3100 | 3300 | 3200 |
| 179 | 3100 | 3500 | 3500 | 3400 | 3200 | 3400 | 3000 | 3500 | 3300 |
| 180 | 3800 | 4100 | 3600 | 3400 | 3400 | 3500 | 3400 | 3400 | 3700 |
| 181 | 4100 | 4200 | 4000 | 4000 | 3400 | 3300 | 3500 | 3400 | 3200 |
| 182 | 3700 | 4100 | 4400 | 4400 | 3500 | 3300 | 3500 | 3500 | 3200 |
| 183 | 3900 | 4100 | 4200 | 4200 | 3800 | 3300 | 3400 | 3400 | 3200 |
| 184 | 3900 | 3800 | 3800 | 4000 | 3700 | 3300 | 3400 | 3000 | 3300 |
| 185 | 4200 | 3800 | 3700 | 3800 | 3200 | 3500 | 3300 | 3200 | 3200 |
| 186 | 3800 | 3800 | 3800 | 3700 | 3300 | 3300 | 3300 | 3400 | 3300 |
| 187 | 3900 | 3800 | 3800 | 3900 | 3500 | 3400 | 3300 | 3600 | 3200 |
| 188 | 4200 | 4100 | 4000 | 4100 | 3500 | 3500 | 3400 | 3600 | 3200 |
| 189 | 4400 | 4400 | 4100 | 4000 | 3500 | 3600 | 3200 | 3500 | 3200 |
| 190 | 4000 | 4200 | 4400 | 4200 | 3500 | 3400 | 3400 | 3300 | 3300 |
| 191 | 4000 | 4100 | 3800 | 4000 | 3700 | 3500 | 3500 | 3300 | 3200 |
| 192 | 4000 | 4100 | 4000 | 4600 | 3700 | 3500 | 3200 | 3500 | |
| 193 | 4400 | 4000 | 3800 | 4100 | 3400 | 3500 | 3200 | 3500 | |
| 194 | 4200 | 3800 | 4200 | 3800 | 3500 | 3500 | | | |
| 195 | 3900 | 3900 | 4500 | 3500 | 3700 | | | | |
| 196 | 3600 | 3700 | 3900 | 3700 | | | | | |
| 197 | 3700 | 3600 | rockpile | rockpile | | | | | |
| 198 | rockpile | rockpile | rockpile | rockpile | | | | | |
| 199 | rockpile | | | | | | | | |
| 200 | | | | | | | | | |
| 201 | | | | | | | | | |
| 202 | | | | | | | | | |
| 203 | | | | | | | | | |
| 204 | | | | | | | | | |
| 205 | | | | | | | | | |
| 206 | | | | | | | | | |
| 207 | | | | | | | | | |
| 208 | | | | | | | | | |
| 209 | | | | | | | | | |
| 210 | | | | | | | | | |
| 211 | | | | | | | | | |
| 212 | | | | | | | | | |
| 213 | | | | | | | | | |
| 214 | | | | | | | | | |
| 215 | | | | | | | | | |
| 216 | | | | | | | | | |
| 217 | | | | | | | | | |

Walk Over Surface Scan

218
219
220



Walk Over Surface Scan


| Coordinates | 186 | 187 | 188 | 189 | 190 | 191 | 192 | 193 | 194 |
|-------------|------|------|------|------|------|------|------|------|------|
| East | | | | | | | | | |
| North | | | | | | | | | |
| 120 | | | | | | | | | |
| 121 | | | | | | | | | |
| 122 | | | | | | | | | |
| 123 | | | | | | | | | |
| 124 | | | | | | | | | |
| 125 | | | | | | | | | |
| 126 | | | | | | | | | |
| 127 | | | | | | | | | |
| 128 | | | | | | | | | |
| 129 | | | | | | | | | |
| 130 | | | | | | | | | |
| 131 | | | | | | | | | |
| 132 | | | | | | | | | |
| 133 | | | | | | | | | |
| 134 | | | | | | | | | |
| 135 | | | | | | | | | |
| 136 | | | | | | | | | |
| 137 | | | | | | | | | |
| 138 | | | | | | | | | |
| 139 | | | | | | | | | |
| 140 | | | | | | | | | |
| 141 | | | | | | | | | |
| 142 | | | | | | | | | |
| 143 | | | | | | | | | |
| 144 | | | | | | | | | |
| 145 | | | | | | | | | |
| 146 | | | | | | | | | |
| 147 | | | | | | | | | |
| 148 | | | | | | | | | |
| 149 | | | | | | | | | |
| 150 | | | | | | | | | |
| 151 | | | | | | | | | |
| 152 | | | | | | | | | |
| 153 | | | | | | | | | |
| 154 | | | | | | | | | |
| 155 | | | | | | | | | |
| 156 | | | | | | | | | |
| 157 | | | | | | | | | |
| 158 | | | | | | | | | |
| 159 | | | | | | | | | |
| 160 | 3300 | 3200 | 3300 | 3700 | 4400 | 3200 | 3200 | 3200 | 3200 |
| 161 | 3400 | 3200 | 3100 | 3000 | 3200 | 3100 | 3300 | 3300 | 3100 |
| 162 | pit | pit | pit | 3000 | 3200 | 3000 | 3400 | 3400 | 3000 |
| 163 | pit | pit | pit | 3000 | 3300 | 3200 | 3400 | 3400 | 3000 |
| 164 | pit | pit | pit | 3200 | 3500 | 3200 | 3000 | 3500 | 3400 |
| 165 | pit | pit | pit | 3300 | 3300 | 3200 | 3100 | 3500 | 3300 |
| 166 | pit | pit | pit | 3200 | 3400 | 3400 | 3200 | 3100 | 3400 |
| 167 | pit | pit | pit | 3100 | 3400 | 3700 | 3400 | 3200 | 3400 |
| 168 | pit | pit | pit | 3200 | 3300 | 3400 | 3300 | 3200 | 3300 |

Walk Over Surface Scan

| Coordinates | 186 | 187 | 188 | 189 | 190 | 191 | 192 | 193 | 194 |
|-------------|------|------|------|------|------|------|------|------|------|
| East | | | | | | | | | |
| North | | | | | | | | | |
| 169 | pit | pit | pit | 3200 | 3300 | 3400 | 3300 | 3300 | 3200 |
| 170 | pit | pit | pit | 3400 | 3000 | 3400 | 3200 | 3300 | 3100 |
| 171 | pit | pit | pit | 3200 | 3200 | 3000 | 3500 | 3400 | 3300 |
| 172 | sw | sw | sw | sw | sw | sw | sw | sw | sw |
| 173 | sw | sw | sw | sw | sw | sw | sw | sw | sw |
| 174 | sw | sw | sw | sw | sw | sw | sw | sw | sw |
| 175 | 3000 | 3000 | 3000 | 3000 | 3200 | 3000 | 3000 | 3300 | 3000 |
| 176 | 3000 | 3000 | 3200 | 3000 | 3000 | 3300 | 3200 | 3400 | 3000 |
| 177 | 3000 | 3000 | 3200 | 3000 | 3000 | 2900 | 3300 | 3700 | 3000 |
| 178 | 3200 | 3000 | 3000 | 3000 | 3100 | 2900 | 3400 | 3400 | 3200 |
| 179 | 3300 | 3100 | 3000 | 3000 | 3000 | 3000 | 3300 | 3300 | 3100 |
| 180 | 3500 | 3200 | 3100 | 3000 | 3000 | 3000 | 3000 | 3500 | 3200 |
| 181 | 3900 | 3000 | 3000 | 3000 | 3100 | 2900 | 3000 | 3500 | 3200 |
| 182 | 3900 | 3100 | 3300 | 2900 | 3000 | 2800 | 3000 | 3300 | 3300 |
| 183 | 3500 | 3200 | 3200 | 2900 | 3000 | 3000 | 3000 | 3000 | 3000 |
| 184 | 3200 | 4500 | 3400 | 3000 | 3000 | 3000 | 3200 | 3000 | 3000 |
| 185 | 3300 | 3900 | 3500 | 3000 | 3000 | 3100 | 3100 | 3000 | 2800 |
| 186 | 3500 | 3900 | 3400 | 3000 | 3200 | 3200 | 3200 | 3000 | 2800 |
| 187 | 3000 | 3500 | 3100 | 3200 | 3200 | 3200 | 3400 | 3000 | 3200 |
| 188 | 3000 | 3200 | 3200 | 3200 | 3000 | 3200 | 3300 | 3100 | |
| 189 | 3200 | 3000 | 3300 | 3300 | | | | | |
| 190 | 3200 | 3200 | 3000 | | | | | | |
| 191 | | | | | | | | | |
| 192 | | | | | | | | | |
| 193 | | | | | | | | | |
| 194 | | | | | | | | | |
| 195 | | | | | | | | | |
| 196 | | | | | | | | | |
| 197 | | | | | | | | | |
| 198 | | | | | | | | | |
| 199 | | | | | | | | | |
| 200 | | | | | | | | | |
| 201 | | | | | | | | | |
| 202 | | | | | | | | | |
| 203 | | | | | | | | | |
| 204 | | | | | | | | | |
| 205 | | | | | | | | | |
| 206 | | | | | | | | | |
| 207 | | | | | | | | | |
| 208 | | | | | | | | | |
| 209 | | | | | | | | | |
| 210 | | | | | | | | | |
| 211 | | | | | | | | | |
| 212 | | | | | | | | | |
| 213 | | | | | | | | | |
| 214 | | | | | | | | | |
| 215 | | | | | | | | | |
| 216 | | | | | | | | | |
| 217 | | | | | | | | | |

Walk Over Surface Scan

218
219
220



Walk Over Surface Scan

| Coordinates | 195 | 196 | 197 | 198 | 199 | 200 | 201 | 202 | 203 |
|-------------|------|------|------|------|------|------|------|------|------|
| East | | | | | | | | | |
| North | | | | | | | | | |
| 120 | | | | | | | | | |
| 121 | | | | | | | | | |
| 122 | | | | | | | | | |
| 123 | | | | | | | | | |
| 124 | | | | | | | | | |
| 125 | | | | | | | | | |
| 126 | | | | | | | | | |
| 127 | | | | | | | | | |
| 128 | | | | | | | | | |
| 129 | | | | | | | | | |
| 130 | | | | | | | | | |
| 131 | | | | | | | | | |
| 132 | | | | | | | | | |
| 133 | | | | | | | | | |
| 134 | | | | | | | | | |
| 135 | | | | | | | | | |
| 136 | | | | | | | | | |
| 137 | | | | | | | | | |
| 138 | | | | | | | | | |
| 139 | | | | | | | | | |
| 140 | | | | | | | | | |
| 141 | | | | | | | | | |
| 142 | | | | | | | | | |
| 143 | | | | | | | | | |
| 144 | | | | | | | | | |
| 145 | | | | | | | | | |
| 146 | | | | | | | | | |
| 147 | | | | | | | | | |
| 148 | | | | | | | | | |
| 149 | | | | | | | | | |
| 150 | | | | | | | | | |
| 151 | | | | | | | | | |
| 152 | | | | | | | | | |
| 153 | | | | | | | | | |
| 154 | | | | | | | | | |
| 155 | | | | | | | | | |
| 156 | | | | | | | | | |
| 157 | | | | | | | | | |
| 158 | | | | | | | | | |
| 159 | | | | | | | | | |
| 160 | 3200 | 3500 | 3500 | 4200 | 3800 | 4000 | | | |
| 161 | 3500 | 3500 | 3500 | 3500 | 3700 | 3700 | 3700 | | |
| 162 | 3500 | 3300 | 3400 | 3500 | 3200 | 3500 | 4000 | 4000 | |
| 163 | 3200 | 3400 | 3500 | 3400 | 3400 | 4000 | 3900 | 3500 | 3500 |
| 164 | 3000 | 3500 | 3500 | 3300 | 3500 | 4000 | 3500 | 3500 | 3800 |
| 165 | 3000 | 3400 | 3400 | 3300 | 3400 | 3900 | 3500 | 3500 | 3800 |
| 166 | 3200 | 3300 | 3300 | 3400 | 3300 | 3500 | 3500 | 3600 | 3500 |
| 167 | 3100 | 3500 | 3800 | 3300 | 3300 | 3500 | 3600 | 3300 | 3300 |
| 168 | 3200 | 3500 | 3400 | 3100 | 3200 | 3000 | 3200 | 3400 | 3400 |

Walk Over Surface Scan

| Coordinates | 195 | 196 | 197 | 198 | 199 | 200 | 201 | 202 | 203 |
|-------------|------|------|------|------|------|------|--------|------|------|
| East | | | | | | | | | |
| North | | | | | | | | | |
| 169 | 3000 | 3500 | 3300 | 3000 | 3200 | 3400 | 3000 | 3400 | 3200 |
| 170 | 3100 | 3400 | 3300 | 3300 | 3100 | 3200 | 3100 | 3300 | 3200 |
| 171 | 3200 | 3200 | 3300 | 3200 | 3000 | 3200 | 3200 | 3100 | 3200 |
| 172 | sw | sw | sw | sw | sw | sw | sw | sw | sw |
| 173 | sw | sw | sw | sw | sw | sw | sw | sw | sw |
| 174 | sw | sw | sw | sw | sw | sw | sw | sw | sw |
| 175 | 3200 | 3000 | 3100 | 3000 | 3100 | | 163000 | 3000 | |
| 176 | 3000 | 3000 | 3200 | 3000 | 3100 | | 3000 | 3000 | |
| 177 | 3100 | 2800 | 3000 | 3200 | 3200 | | 3100 | 4000 | |
| 178 | 3100 | 3000 | 3000 | 3000 | 3200 | | 3100 | | |
| 179 | 3200 | 3000 | 3000 | 3100 | 3000 | | 3200 | | |
| 180 | 3200 | 3200 | 3200 | 3000 | 3000 | 3100 | 3200 | 3200 | |
| 181 | 3200 | 3300 | 3100 | 3400 | 2800 | 3200 | 3100 | | |
| 182 | 3200 | 3500 | 3300 | 3300 | 3000 | 3200 | | | |
| 183 | 3100 | 3400 | 3200 | 3200 | 3300 | | | | |
| 184 | 3100 | 3400 | 3200 | 3500 | | | | | |
| 185 | 3200 | 3200 | 3200 | | | | | | |
| 186 | 3200 | 3200 | | | | | | | |
| 187 | 3200 | | | | | | | | |
| 188 | | | | | | | | | |
| 189 | | | | | | | | | |
| 190 | | | | | | | | | |
| 191 | | | | | | | | | |
| 192 | | | | | | | | | |
| 193 | | | | | | | | | |
| 194 | | | | | | | | | |
| 195 | | | | | | | | | |
| 196 | | | | | | | | | |
| 197 | | | | | | | | | |
| 198 | | | | | | | | | |
| 199 | | | | | | | | | |
| 200 | | | | | | | | | |
| 201 | | | | | | | | | |
| 202 | | | | | | | | | |
| 203 | | | | | | | | | |
| 204 | | | | | | | | | |
| 205 | | | | | | | | | |
| 206 | | | | | | | | | |
| 207 | | | | | | | | | |
| 208 | | | | | | | | | |
| 209 | | | | | | | | | |
| 210 | | | | | | | | | |
| 211 | | | | | | | | | |
| 212 | | | | | | | | | |
| 213 | | | | | | | | | |
| 214 | | | | | | | | | |
| 215 | | | | | | | | | |
| 216 | | | | | | | | | |
| 217 | | | | | | | | | |

Walk Over Surface Scan

| Coordinates | 204 | 205 |
|-------------|------|------|
| East | | |
| North | | |
| 169 | 3300 | 3000 |
| 170 | 3200 | 3200 |
| 171 | 3200 | 3300 |
| 172 | sw | sw |
| 173 | sw | sw |
| 174 | sw | sw |
| 175 | | |
| 176 | | |
| 177 | | |
| 178 | | |
| 179 | | |
| 180 | | |
| 181 | | |
| 182 | | |
| 183 | | |
| 184 | | |
| 185 | | |
| 186 | | |
| 187 | | |
| 188 | | |
| 189 | | |
| 190 | | |
| 191 | | |
| 192 | | |
| 193 | | |
| 194 | | |
| 195 | | |
| 196 | | |
| 197 | | |
| 198 | | |
| 199 | | |
| 200 | | |
| 201 | | |
| 202 | | |
| 203 | | |
| 204 | | |
| 205 | | |
| 206 | | |
| 207 | | |
| 208 | | |
| 209 | | |
| 210 | | |
| 211 | | |
| 212 | | |
| 213 | | |
| 214 | | |
| 215 | | |
| 216 | | |
| 217 | | |

Walk Over Surface Scan

218
219
220



Attachment 2

Revised Final Survey Report

REVISED FINAL SURVEY REPORT

**TEXAS INSTRUMENTS INCORPORATED
BURIAL SITE
Attleboro, Massachusetts**

Prepared by

Creative Pollution Solutions, Inc.

1/8/93

revision 1.0

INTRODUCTION

This revised post excavation survey report is intended as an addendum to the initial "Post Excavation Radiological Survey Report" submitted by Texas Instruments Incorporated to the NRC on 12/1/92. This report shows the areas where additional excavation took place on the site and the method for defining the extent of the excavation. This report does not include a walk-over survey of the entire affected area, however, this will be included in a later report to the NRC.

The conclusion of the survey conducted by ORISE for the NRC, on December 14-16 1992, was that the bottom of the excavation was at acceptable levels, however, there was some question on areas around the wall of the excavation. NRC requested that Texas Instruments continue to excavate in certain areas and that Texas Instruments demonstrate that the extent of the excavation is appropriate.

To address these issues Texas Instruments Incorporated (TI) performed additional excavation in areas where the walls of the excavation were above background radiation levels (using NaI measurements). In addition, to demonstrate that the excavation had been extended far enough TI performed split spoon sampling around the perimeter of the excavation (see Appendix A).

While a complete walk-over survey has not yet been completed all elevated areas identified during the ORISE survey or identified in the initial Post Excavation Survey report were addressed. In some cases the entire excavation area was extended while in other cases the surface of the area was scraped to removed the contaminated material. A complete walk-over survey will be included in a final report to the NRC.

PERIMETER SPLIT SPOON SAMPLING

As a means of demonstrating that the walls of the excavated area were at or below the approved guidance levels of 30 picocuries total uranium per gram of soil (pCi/g), a perimeter split spoon sampling plan was implemented. Initially, the walls of the excavation were surveyed to determine that the exposed wall (above the water) was at background levels (on the NaI meter). In areas where greater than background levels were found the excavation was extended. When all of the walls were found to be at background levels split spoon samples were taken to a depth of 6 feet. These samples were taken approximately 1-5 meters back from the wall of the excavation and were spaced approximately every 5-10 meters around the entire excavated area. Sampling results are included in Appendix A and locations are shown on the map in figure 1. In cases where past data was available the area was not resampled but, rather, the previous data was used as documentation.

SURFACE SOIL SAMPLING WITHIN THE EXCAVATED AREA

In areas where significant additional excavation took place, whenever possible, surface soil samples were taken on the floor of the excavation. In many locations these samples were composites, taken from the floor of the excavation, through the water, with a backhoe. These results are shown in Appendix B and sample locations are shown on the map in figure 1.

Appendix A

Split Spoon Samples Excavation Perimeter

Alpha screen (pCi/g)

| <u>North</u> | <u>East</u> | <u>0-2'</u> | <u>2-4'</u> | <u>4-6'</u> |
|--------------|-------------|-------------|-------------|-------------|
| 200 | 125 | 12 | 10 | 11 |
| 206 | 130 | 14 | 24 | 10 |
| 200 | 135 | 15 | 9 | 14 |
| 200 | 140 | 29 | 14 | 8 |
| 200 | 145 | 12 | 15 | 5 |
| 205 | 145 | 21 | 16 | 9 |
| 210 | 165 | 11 | 21 | 13 |
| 205 | 153 | 8 | 12 | 23 |
| 195 | 135 | 25 | 11 | refusal |
| 175 | 185 | 18 | 21 | 10 |
| 190 | 174 | 32 | 5 | 8 |
| 175 | 163 | 9 | 5 | 8 |
| 175 | 165 | 17 | 4 | 6 |
| 180 | 175 | 13 | 10 | 5 |
| 175 | 168 | 13 | 15 | 37 |
| 145 | 135 | 33 | 23 | 18 |
| 155 | 145 | 9 | 18 | 13 |

Alpha screen (pCi/g)

| <u>North</u> | <u>East</u> | <u>0-2'</u> | <u>2-4'</u> | <u>4-6'</u> |
|--------------|-------------|-------------|-------------|------------------------|
| 175 | 175 | 7 | 5 | 9 |
| 185 | 162 | 7 | 5 | 11 |
| 140 | 125 | 29 | 20 | 18 |
| 140 | 103 | 17 | 13 | 16 |
| 178 | 98 | 19 | 7 | refusal |
| 135 | 115 | 17 | 18 | 15 |
| 130 | 110 | 13 | 18 | 10 |
| 165 | 85 | 15 | 18 | 25 |
| 150 | 90 | 8 | 8 | refusal |
| 210 | 150 | 34 | 25 | 24 |
| 172.5 | 85 | 12 | 13 | 15 |
| 175 | 90 | 16 | 13 | no sample (water line) |

Split spoon results from prior sampling (11/6/92)

Alpha screening (pCi/g)

| <u>North</u> | <u>East</u> | <u>0-1'</u> | <u>1-2'</u> | <u>2-3'</u> | <u>3-4'</u> | <u>4-5'</u> | <u>5-6'</u> |
|--------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|
| 145 | 95 | 10 | 31 | 17 | | 22 | |
| 145 | 140 | 27 | 34 | 10 | 10 | 9 | |
| 190 | 120 | 18 | 21 | 15 | | 15 | |
| 202 | 170 | 11 | 16 | | | 12 | |
| 170 | 150 | 9 | 12 | 6 | 5 | 7 | |

Split spoon results from prior sampling (7/25/92)

Alpha screening (pCi/g)

| <u>North</u> | <u>East</u> | <u>.5 meter</u> | <u>1 meter</u> | <u>1.5 meter</u> | <u>2 meter</u> |
|--------------|-------------|-----------------|----------------|------------------|----------------|
| 145 | 145 | 12 | 10 | | |
| 175 | 105 | 9 | 9 | | |
| 190 | 115 | 15 | 11 | | |
| 210 | 130 | 11 | 5 | | |
| 202 | 160 | 16 | 11 | | |
| 200 | 170 | 9 | 6 | | |
| 172.5 | 160 | 8 | 8 | | |
| 177.5 | 140 | 20 | 9 | 6 | 13 |
| 147.5 | 125 | 10 | 6 | | |

Appendix B

Additional soil samples from Excavated Area

| <u>North</u> | <u>East</u> | <u>Alpha screening (pCi/g)</u> |
|--------------|-------------|--------------------------------|
| 170 | 95 | 21 |
| 165 | 95 | 31 |
| 155 | 95 | 37 |
| 165 | 105 | 24 |
| 155 | 105 | 24 |
| 145 | 100 | 10 |
| 150 | 97.5 | 19 |